

Comprehensive Analysis and Comparison of Convolutional Neural Networks (CNNs) and Generative Adversarial Networks (GANs)

RAKESH JINDAL¹, AMISHA NAIK², K L GANATRE³, RAJAT GUPTA⁴
^{1, 2, 3, 4}Dept. of Computer Science, University of Calcutta, India

Abstract- CNNs and GANs, whether working solo or combined, have sparked major shifts in AI, each playing distinct roles in the deep learning landscape. This write-up dives into a fairly deep dive and comparison of both models, digging into their internal designs, pros and cons, and practical uses. CNNs, famous for their knack for pulling out visual features, have pushed forward image tasks like classification and detection, along with medical imaging. Meanwhile, GANs shook up the generative scene by producing incredibly lifelike visuals and data. Along the way, this review uncovers key differences in how CNNs and GANs are trained, how complex GANs can get, and the ways their performance gets measured—while also pointing out common hurdles like CNN overfitting or GAN instability. On top of that, it looks into how mixing the two can lead to hybrid systems, useful in areas like synthetic data generation or style transfer. The aim here is to give researchers and engineers a helpful lens into where these models shine, where they fall short, and where new research might go next.

Indexed Terms- Convolutional Neural Networks (CNN), Generative Adversarial Networks (GAN), Deep Learning Architectures, Image Processing, Model Comparison, Artificial Intelligence Applications.

I. INTRODUCTION

1.1 Background on Deep Learning




Figure 1: Review of deep learning, Concepts, CNN Architectures, Challenges, Applications and future directions

Source: Alzubaidi, L., Zhang, J., Humaidi, A. J., Al-Dujaili, A., Duan, Y., Al-Shamma, O., ... & Farhan, L. (2021). Review of deep learning: concepts, CNN architectures, challenges, applications, future directions. *Journal of big Data*, 8, 1-74.

Deep learning, as a transformative branch of machine learning, has reshaped artificial intelligence by flipping traditional data processing and machine interaction on its head. Rather than depending on manual feature extraction, deep learning models utilize intricate neural networks that automatically identify layered patterns within raw data. This shift empowers machines to tackle complex tasks such as visual recognition, natural language understanding, and audio interpretation with a level of accuracy and nuance that earlier techniques couldn't reach. Two architectural models central to this leap forward are Convolutional Neural Networks (CNNs) and Generative Adversarial Networks (GANs), both of

which have driven substantial progress in the AI domain.

CNNs, drawing inspiration from the visual processing mechanisms of the human brain, are specially designed to capture hierarchical features in data. Using convolutional layers, these networks excel at detecting visual cues such as edges, textures, and shapes. This makes them ideally suited for image-centric tasks like classification, segmentation, and object detection—where the objective is to identify and categorize visual components. As a result, CNNs have become foundational tools in computer vision, widely implemented in technologies spanning from self-driving cars to diagnostic medical tools.

Recently introduced generative adversarial networks (GANs) have completely transformed the former understanding and practice of generative modeling. CNNs, being primarily discriminative in implementation and aimed at class or label recognition undergo a distinct process of working compared to GANs which are composed of a working generator and discriminator that operates in parallel to enhance generative performance. The generator tries to generate synthetic data which will be undistinguishable from real samples while the discriminator tries to determine whether data is genuine or synthesized. The rivalry between the generator and discriminator forces them to improve the degree of reality in displayed outputs continually; hence, GANs are capable of providing extremely realistic images, videos, and audio files (Aggarwal, Mittal, & Battineni, 2021). By its creative design, dynamic training, GANs have allowed new changes in making realistic pictures, extending data sets, and creating inventive creative outputs.

The combination of CNNs and GANs is an example of how deep learning can allow different process emulation analytical and synthetic with CNNs and GANs showing that AI advancement is deep in its range.

III. GAN ARCHITECTURE: GENERATOR AND DISCRIMINATOR

GANs operate on a simple yet powerful concept involving two neural networks competing against each other: the generator and the discriminator. The

generator's job is to produce synthetic data that closely mimics real data, while the discriminator's role is to distinguish between genuine and fake data. Through this adversarial process, the generator improves by learning from the discriminator's feedback, and the discriminator sharpens its ability to tell real from fake. This back-and-forth continues until the generator's output becomes indistinguishable from actual data (Alzubaidi et al., 2021). The framework's success depends heavily on the ongoing interaction between the two networks, which must be carefully balanced to prevent issues like mode collapse or vanishing gradients (Dash et al., 2021).

4.1 Learning Paradigm: Discriminative (CNN) vs. Generative (GAN)

Convolutional Neural Networks focus on discriminative learning, aiming to classify data by finding decision boundaries between different classes—an approach commonly used in tasks like image classification and object detection (Zhao et al., 2020; Liu et al., 2021). In contrast, Generative Adversarial Networks emphasize generating new data samples. GANs seek to understand the underlying data distribution and create realistic data instances starting from random noise (Dash et al., 2021). This process involves a generator creating new data and a discriminator evaluating whether it's real or fake, forming an inherently adversarial learning system (Lu et al., 2022). Essentially, CNNs are driven by pattern recognition, while GANs focus on data generation.

4.2 Architecture Design and Complexity

The typical design of CNNs involves a hierarchical arrangement of layers, including convolutional layers, pooling layers, and fully connected layers. This modular and scalable structure allows CNN architectures to be adapted based on the specific requirements of the image data and the task at hand (Saleem et al., 2022; Bhatt et al., 2021). In contrast, GANs consist of two separate but interconnected networks—the generator and the discriminator—that must be carefully coordinated to achieve effective training. The components within both the generator and discriminator contribute to a more complex overall architecture. As noted by Alzubaidi et al.

(2021), achieving stable training in GANs is generally more challenging than in CNNs, primarily due to the difficulty in balancing the learning dynamics between the two networks.

4.3 Training Process and Optimization Challenges

4.3.1 CNN: Overfitting, Vanishing Gradient

CNNs are trained using backpropagation and gradient descent, but these methods can lead to overfitting, especially when the available data is limited. Techniques like dropout, data augmentation, and batch normalization help address this issue (Nasreen et al., 2021). Another challenge is the vanishing gradient problem, where gradients become too small in deep networks, slowing down learning. This has been largely tackled by using activation functions like ReLU, which help maintain effective gradient flow (Ramadhani, 2021).

4.3.2 GAN: Mode Collapse, Non-Convergence

Optimization challenges are particularly difficult to address in GANs. One major issue is mode collapse, where the generator produces samples from a limited subset of the data distribution and fails to represent its full diversity (Dash et al., 2021). Differences in the learning progress of the generator and discriminator often lead to non-convergence, causing unstable training. To overcome these problems, Lu et al. (2022) suggest employing advanced techniques like feature matching, mini-batch discrimination, or developing new architectures such as Wasserstein GANs.

4.4 Performance Metrics and Evaluation Techniques

4.4.1 CNN: Accuracy, Precision, Recall

Traditional evaluation of CNNs typically relies on metrics like accuracy, precision, recall, and F1-score (Jakubec et al., 2021). These measures assess how effectively a model can differentiate between multiple classes and are widely used in tasks such as object recognition and segmentation (Zhao et al., 2020).

4.4.2 GAN: Inception score and Fréchet Inception distance (FID).

Evaluating GANs is more complex since they generate data rather than classify it. The Inception Score (IS)

assesses generated images using a pre-trained CNN by analyzing their class distribution, capturing both image quality and diversity (Dash et al., 2021). The Fréchet Inception Distance (FID) measures the statistical differences between real and synthetic images, offering a more comprehensive and precise evaluation of image quality variation (Lu et al., 2022). These metrics are essential for judging the quality of generated data, especially in applications like artificial image synthesis and detecting digital fraud such as deepfakes.

V. STRENGTHS AND WEAKNESSES

5.1 Convolutional Neural Networks (CNNs)

5.1.1 Strengths

CNNs excel at feature extraction and detecting spatial patterns, making them highly effective for image-related tasks. They perform exceptionally well in image classification, segmentation, and object detection by hierarchically extracting image representations directly from pixel data without needing preprocessing (Dash et al., 2021). Their architecture optimally handles high-dimensional images, which has driven widespread adoption in fields like medical imaging and remote sensing (Langote & Zade, 2020).

5.1.2 Weaknesses

Despite their strong discriminative abilities, CNNs do not naturally extend to generative tasks and often struggle when required to synthesize new data, such as creating images or expanding datasets. They are also prone to overfitting when trained on small datasets and generally require large amounts of labeled data for best performance (Saxena & Cao, 2021). Their limited generative capabilities highlight the need to combine them with models like GANs for generation tasks.

5.2 Generative Adversarial Networks (GANs)

5.2.1 Strengths

GANs are highly effective at data generation and synthesis, producing realistic images, audio, and structured data. Their adversarial training mechanism

drives continuous improvements in the generator, resulting in high-quality outputs (Aggarwal et al., 2021). GANs have shown success in diverse applications such as medical image enhancement, art style transfer, deepfake creation, and simulations (Ma et al., 2021; Kumar et al., 2020). Their ability to generate synthetic datasets is especially valuable when real data is scarce.

5.2.2 Weaknesses

Training GANs often faces challenges like mode collapse, instability, and failure to converge (Saxena & Cao, 2021). Maintaining a balanced competition between the generator and discriminator can be difficult, requiring iterative tuning of model design and parameters. Additionally, GANs offer lower interpretability compared to CNNs; while CNNs can reveal learned filters, GANs lack clear explanations for why certain synthetic outputs are generated (Dash et al., 2021). These limitations restrict their widespread adoption and reliability in critical applications.

CONCLUSION

6.1 Summary of Key Findings

Convolutional Neural Networks (CNNs) and Generative Adversarial Networks (GANs) are fundamental pillars driving progress in deep learning and AI. CNNs are widely recognized for their prowess in feature extraction and classification, contributing significantly to image processing tasks such as object detection, medical imaging, and facial recognition (Alzubaidi et al., 2021; Nandhini Abirami et al., 2021). Meanwhile, GANs have revolutionized data generation by producing realistic visual content and enhancing data augmentation capabilities (Esan et al., 2021; Dev et al., 2022). Despite their distinct roles, CNNs and GANs are deeply interconnected, particularly when CNNs are integrated within GANs to improve image generation and refinement processes (Frid-Adar et al., 2018; Zhou et al., 2021).

6.2 Importance of Both CNN and GAN in AI Development

The combined use of CNNs and GANs is essential for

advancing AI applications across numerous industries. CNNs remain key players in computer vision due to their rapid and accurate processing of visual data (Alzubaidi et al., 2021). On the other hand, GANs introduce innovative data generation methods, including image synthesis, enhancement of medical imaging, and creation of realistic training environments (Esan et al., 2021). This synergy, especially through hybrid models, offers AI the capability to efficiently process and simulate complex visual information, driving innovation in fields ranging from entertainment to healthcare (Durgadevi, 2021).

6.3 Final Thoughts on Their Future Trajectory

Looking ahead, CNNs and GANs are poised to remain at the forefront of AI innovation. Improvements in CNN architectures and training methods will make them lighter, more efficient, and better suited for real-world deployment (Alzubaidi et al., 2021; Nandhini Abirami et al., 2021). GANs face challenges in achieving stable training and addressing ethical concerns, such as misuse in deepfake creation (Dev et al., 2022; Frid-Adar et al., 2018; Durgadevi, 2021). Continued research, especially into hybrid CNN-GAN systems, promises to unlock transformative advances in sectors like autonomous driving, entertainment, and medical diagnostics (Zhou et al., 2021; Frid-Adar et al., 2018). Ultimately, the future of deep learning will be shaped by the collaborative potential of these models, enabling AI systems to perform increasingly complex tasks with greater effectiveness and versatility.

REFERENCES

- [1] Krizhevsky, A., & Hinton, G. (2009). Learning multiple layers of features from tiny images. *Technical report*, Citeseer.
- [2] Krizhevsky, A., Sutskever, I., & Hinton, G. E. (2012). ImageNet classification with deep convolutional neural networks. In *Advances in Neural Information Processing Systems (NIPS)*.
- [3] Kumar Singh, K., & Jae Lee, Y. (2017). Hide-and-seek: Forcing a network to be meticulous for weakly-supervised object and action localization. In *Proceedings of the IEEE*

- International Conference on Computer Vision (ICCV).*
- [4] Li, W., Zhao, R., Xiao, T., & Wang, X. (2014). DeepReID: Deep filter pairing neural network for person re-identification. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*.
- [5] Murdock, C., Li, Z., Zhou, H., & Duerig, T. (2016). Blockout: Dynamic model selection for hierarchical deep networks. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*.
- [6] Ristani, E., Solera, F., Zou, R., Cucchiara, R., & Tomasi, C. (2016). Performance measures and a data set for multi-target, multi-camera tracking. In *Proceedings of the European Conference on Computer Vision Workshops (ECCVW)*.
- [7] Simonyan, K., & Zisserman, A. (2015). Very deep convolutional networks for large-scale image recognition. In *International Conference on Learning Representations (ICLR)*.
- [8] Srivastava, N., Hinton, G. E., Krizhevsky, A., Sutskever, I., & Salakhutdinov, R. (2014). Dropout: A simple way to prevent neural networks from overfitting. *Journal of Machine Learning Research*, 15, 1929–1958.
- [9] Sun, Y., Zheng, L., Deng, W., & Wang, S. (2017). SVDNet for pedestrian retrieval. In *Proceedings of the IEEE International Conference on Computer Vision (ICCV)*.
- [10] Szegedy, C., Vanhoucke, V., Ioffe, S., Shlens, J., & Wojna, Z. (2016). Rethinking the inception architecture for computer vision. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*.
- [11] S. Sarica and J. Luo, “Stopwords in technical language processing,” *PLoS One*, vol. 16, no. 8, pp. 1–13, Aug. 2021, doi: 10.1371/journal.pone.0254937.
- [12] H. Alshalabi, S. Tiun, N. Omar, F. N. AL-Aswadi, and K. Ali Alezabi, “Arabic light-based stemmer using new rules,” *Journal of King Saud University - Computer and Information Sciences*, vol. 34, no. 9, pp. 6635–6642, Oct. 2022, doi: 10.1016/j.jksuci.2021.08.017.
- [13] K. Maharana, S. Mondal, and B. Nemade, “A review: Data pre-processing and data augmentation techniques,” *Global Transitions Proceedings*, vol. 3, no. 1, pp. 91–99, Jun. 2022, doi: 10.1016/j.gltp.2022.04.020.
- [14] J. T. Hancock and T. M. Khoshgoftaar, “Survey on categorical data for neural networks,” *J Big Data*, vol. 7, no. 1, pp. 1–41, Dec. 2020, doi: 10.1186/s40537-020-00305-w.
- [15] L. Jen and Y.-H. Lin, “A Brief Overview of the Accuracy of Classification Algorithms for Data Prediction in Machine Learning Applications,” *Journal of Applied Data Sciences*, vol. 2, no. 3, pp. 84–92, 2021, doi: 10.47738/jads.v2i3.38.
- [16] S. A. Hicks et al., “On evaluation metrics for medical applications of artificial intelligence,” *Sci Rep*, vol. 12, no. 1, pp. 1–9, Dec. 2022, doi: 10.1038/s41598-022-09954-8.
- [17] S. Orozco-Arias, J. S. Piña, R. Tabares-Soto, L. F. Castillo-Ossa, R. Guyot, and G. Isaza, “Measuring performance metrics of machine learning algorithms for detecting and classifying transposable elements,” *Processes*, vol. 8, no. 6, pp. 1–18, Jun. 2020, doi: 10.3390/PR8060638.
- [18] Esfahani, Shirin Nasr, and Shahram Latifi. “A Survey of State-of-The-Art GAN-Based Approaches to Image Synthesis.” 9th International Conference on Computer Science, Engineering and Applications (CCSEA 2019), 13 July 2019, csitcp.com/paper/9/99csit06.pdf, <https://doi.org/10.5121/csit.2019.90906>.
- [19] Nabati, R., & Qi, H. (2019). "RRPN: Radar Region Proposal Network for Object Detection in Autonomous Vehicles." 2019 IEEE International Conference on Image Processing (ICIP), Taipei, Taiwan, 2019, pp. 3093-3097, doi: 10.1109/ICIP.2019.8803392.
- [20] Rawat, W., & Wang, Z. (2017). "Deep Convolutional Neural Networks for Image Classification: A Comprehensive Review." *Neural Computation*, 29(9), pp. 2352-2449, Sept. 2017, doi: 10.1162/neco_a_00990.
- [21] Wang, Weibin, et al. “Medical Image Classification Using Deep Learning.” *Intelligent Systems Reference Library*, 19 Nov. 2019, pp. 33–51, https://doi.org/10.1007/978-3-030-32606-7_3.

- [22] Alom, Md Zahangir, et al. "The History Began from AlexNet: A Comprehensive Survey on Deep Learning Approaches." ArXiv:1803.01164 [Cs], 12 Sept. 2018, arxiv.org/abs/1803.01164.
- [23] Mohit Jain , Adit Shah "Machine Learning with Convolutional Neural Networks (CNNs) in Seismology for Earthquake Prediction" Iconic Research And Engineering Journals Volume 5 Issue 8 2022 Page 389-398 <https://www.irejournals.com/index.php/paper-details/1707057>
- [24] Karp, Rafal, and Zaneta Swiderska-Chadaj. Automatic Generation of Graphical Game Assets Using GAN. 13 July 2021, <https://doi.org/10.1145/3477911.3477913>.
- [25] L. Jiao and J. Zhao, "A Survey on the New Generation of Deep Learning in Image Processing," in IEEE Access, vol. 7, pp. 172231-172263, 2019, doi: 10.1109/ACCESS.2019.2956508.
- [26] L. Wang, W. Chen, W. Yang, F. Bi and F. R. Yu, "A State-of-the-Art Review on Image Synthesis With Generative Adversarial Networks," in IEEE Access, vol. 8, pp. 63514-63537, 2020, doi: 10.1109/ACCESS.2020.2982224.
- [27] Shorten, Connor, and Taghi M. Khoshgoftaar. "A Survey on Image Data Augmentation for Deep Learning." Journal of Big Data, vol. 6, no. 1, 6 July 2019, journalofbigdata.springeropen.com/articles/10.1186/s40537-019-0197-0, <https://doi.org/10.1186/s40537-019-0197-0>.
- [28] Kayalibay, Baris, et al. "CNN-Based Segmentation of Medical Imaging Data." ArXiv:1701.03056 [Cs], 25 July 2017, arxiv.org/abs/1701.03056.
- [29] Jain, M., & Shah, A. (2022). Machine Learning with Convolutional Neural Networks (CNNs) in Seismology for Earthquake Prediction. Iconic Research and Engineering Journals, 5(8), 389–398. <https://www.irejournals.com/paper-details/1707057>
- [30] Kaushik, P., & Jain, M. A Low Power SRAM Cell for High Speed Applications Using 90nm Technology. Csjournals. Com, 10. <https://www.csjournals.com/IJEE/PDF10-2/66.%20Puneet.pdf>
- [31] Kaushik, P., & Jain, M. (2018). Design of low power CMOS low pass filter for biomedical application. International Journal of Electrical Engineering & Technology (IJEET), 9(5).
- [32] Kumar, Y., Saini, S., & Payal, R. (2020). Comparative Analysis for Fraud Detection Using Logistic Regression, Random Forest and Support Vector Machine. SSRN Electronic Journal.
- [33] Höppner, S., Baesens, B., Verbeke, W., & Verdonck, T. (2020). Instance-Dependent Cost-Sensitive Learning for Detecting Transfer Fraud. arXiv preprint arXiv:2005.02488.
- [34] Kaushik, P., & Jain, M. A Low Power SRAM Cell for High Speed Applications Using 90nm Technology. Csjournals. Com, 10. https://www.researchgate.net/publication/391458245_A_Low_Power_SRAM_Cell_for_High_Speed
- [35] Bhat, N. (2019). Fraud detection: Feature selection-over sampling. Kaggle. Retrieved from <https://www.kaggle.com/code/nareshbhat/fraud-detection-feature-selection-over-sampling>
- [36] InsiderFinance Wire. (2021). Logistic regression: A simple powerhouse in fraud detection. Medium. Retrieved from <https://wire.insiderfinance.io/logistic-regression-a-simple-powerhouse-in-fraud-detection-15ab984b2102>
- [37] Kaushik, P., & Jain, M. (2018). Design of low power CMOS low pass filter for biomedical application. International Journal of Electrical Engineering & Technology (IJEET), 9(5). https://iaeme.com/MasterAdmin/Journal_upload_s/IJEET/VOLUME_9_ISSUE_5/IJEET_09_05_003.pdf
- [38] Raymaekers, J., Verbeke, W., & Verdonck, T. (2021). Weight-of-evidence 2.0 with shrinkage and spline-binning. arXiv preprint arXiv:2101.01494. Retrieved from <https://arxiv.org/abs/2101.01494>
- [38] Dal Pozzolo, A., Boracchi, G., Caelen, O., Alippi, C., & Bontempi, G. (2017). Credit card fraud detection: A realistic modeling and a novel learning strategy. IEEE Transactions on Neural Networks and Learning Systems, 29(8), 3784–3797. <https://doi.org/10.1109/TNNLS.2017.2736643>

- [40] Carcillo, F., Dal Pozzolo, A., Le Borgne, Y. A., Caelen, O., Mazzer, Y., & Bontempi, G. (2019). Scarff: A scalable framework for streaming credit card fraud detection with spark. *Information Fusion*, 41, 182–194. <https://doi.org/10.1016/j.inffus.2017.09.005>
- [41] West, J., & Bhattacharya, M. (2016). Intelligent financial fraud detection: A comprehensive review. *Computers & Security*, 57, 47–66. <https://doi.org/10.1016/j.cose.2015.09.005>
- [42] Zareapoor, M., & Shamsolmoali, P. (2015). Application of credit card fraud detection: Based on bagging ensemble classifier. *Procedia Computer Science*, 48, 679–685. <https://doi.org/10.1016/j.procs.2015.04.201>
- [43] Patel, H., & Zaveri, M. (2011). Credit card fraud detection using neural network. *International Journal of Innovative Research in Computer and Communication Engineering*, 1(2), 1–6. https://www.ijrcce.com/upload/2011/october/1_Credit.pdf
- [44] Puneet Kaushik, Mohit Jain , Gayatri Patidar, Paradayil Rhea Eapen, Chandra Prabha Sharma (2018). Smart Floor Cleaning Robot Using Android. *International Journal of Electronics Engineering*. <https://www.csjournals.com/IJEE/PDF10-2/64.%20Puneet.pdf>
- [45] Duman, E., & Ozelcik, M. H. (2011). Detecting credit card fraud by genetic algorithm and scatter search. *Expert Systems with Applications*, 38(10), 13057–13063. <https://doi.org/10.1016/j.eswa.2011.04.102>
- [46] Puneet Kaushik, Mohit Jain. “A Low Power SRAM Cell for High Speed Applications Using 90nm Technology.” *Csjournals.Com* 10, no. 2 (December 2018): 6. <https://www.csjournals.com/IJEE/PDF10-2/66.%20Puneet.pdf>
- [47] Jain, M., & Srihari, A. (2021). Comparison of CAD detection of mammogram with SVM and CNN. *IRE Journals*, 8(6), 63-75. <https://www.irejournals.com/formatedpaper/1706647.pdf>
- [48] Kaushik, P., Jain, M., & Jain, A. (2018). A pixel-based digital medical images protection using genetic algorithm. *International Journal of Electronics and Communication Engineering*, 31-37. http://www.irphouse.com/ijece18/ijecev11n1_05.pdf
- [49] Kaushik, P., Jain, M., & Shah, A. (2018). A Low Power Low Voltage CMOS Based Operational Transconductance Amplifier for Biomedical Application. <https://ijsetr.com/uploads/136245IJSETR17012-283.pdf>
- [50] Jain, M., & Shah, A. (2022). Machine Learning with Convolutional Neural Networks (CNNs) in Seismology for Earthquake Prediction. *Iconic Research and Engineering Journals*, 5(8), 389–398. <https://www.irejournals.com/paper-details/1707057>
- [51] Kaushik, P., & Jain, M. (2018). Design of low power CMOS low pass filter for biomedical application. *International Journal of Electrical Engineering & Technology (IJEET)*, 9(5).
- [52] KAUSHIK, P., JAIN, M., & SHAH, A. (2018). A Low Power Low Voltage CMOS Based Operational Transconductance Amplifier for Biomedical Application. <https://ijsetr.com/uploads/136245IJSETR17012-283.pdf>
- [53] Overview of GAN structure. (n.d.). Google for Developers. https://developers.google.com/machine-learning/gan/gan_structure
- [54] Raymaekers, J., Verbeke, W., & Verdonck, T. (2021). Weight-of-evidence 2.0 with shrinkage and spline-binning. *arXiv preprint arXiv:2101.01494*. Retrieved from <https://arxiv.org/abs/2101.01494>