Toward Responsible Deployment of On Device Language Models: A Framework for Privacy Centric Evaluation and Regulatory Alignment

DEEPAK KEJRIWAL[1], SAURABH KANSAL[2]

Abstract- The integration of large language models (LLMs) into mobile and edge devices heralds a paradigm shift in personalized, low latency AI experiences. Yet on the other side, a plethora of concerns arise regarding user privacy, regulation, and adversarial robustness. Till date, there remain certain shortcomings inherent to methodologies assessing privacy risks (e.g., red teaming, privacy probes) that could not be adequately extended to resource constrained environments, such as smartphones or embedded systems. We introduce an encompassing multilayer framework for evaluating and mitigating privacy risks of on device LLMs. This includes synthetic data injection, differential audit trails, and consent aware tracing mechanisms that go hand in hand with developments in privacy regulations such as the EU AI Act and data protection laws at the U.S. state level. Based on real-world case studies ranging from messaging to voice assistant platforms, we investigate the challenges of implementation and regulatory incoherence and technical approaches that can help bridge the chasm between theoretical compliance and actual deployment. The hybrid result of these studies emphasizes that embedding regulatory principles within LLM system architectures is the initiative toward responsible AI in real-time privacy-sensitive settings.

Indexed Terms- On-device LLMs, Privacy centric AI, AI regulation, EU AI Act, Data protection, Consent aware tracing, Red teaming, Edge AI, Regulatory alignment, Privacy leakage

I. INTRODUCTION

1.1 Background and Motivation

The advent of GPT and its derivatives forever changed the natural language understanding, generation, and interaction paradigms across industries. Traditionally confined to powerful cloud computation environments, LLMs are now increasingly being deployed in mobile and edge devices, supporting offline functionality, reducing latency, and increasing user personalization (Xu et al., 2024). While such a shift is exciting from a technical standpoint, it entails multiple complex and pressing challenges with respect to user data privacy, compliance with regulatory measures, and ethical deployment.

LLMs operating at a relatively closer distance to the end user observe a highly sensitive contextual data set comprising private messages, voice commands, behavioral profiling, metadata, etc. The prospects of such models memorizing, reproducing, or leaking this was a red flag from both a technical and legal viewpoint (Kibriya et al., 2024; Zhou et al., 2024). Recent works have shown that certain instances of LLMs have, on occasions, disclosed private user data through inferring outputs when posed adversarial prompts or during red teaming exercises (Pujari & Pakina, 2023). Such risks are exacerbated by the opacity of the LLM training pipeline and the near-impossible task of tracing back the source of a particular behavior in a model.

On the other hand, regulatory bodies across the globe started drafting stringent AI laws that address and restrict cases of data misuse, insist on model transparency, and protect the rights of users. The EU AI Act, for instance, designates different tiers of risk and maps these to traceability and human oversight requirements, while U.S. state level laws such as the California Consumer Privacy Act (CCPA) articulate requirements for opt-in data use, consent, and auditability (Gaurav et al., 2024). However, despite these legislative advancements, a marked gap continues to exist between the abstract requirements laid out in such policies and the concrete technical implementations found in AI systems, especially those deployed in decentralized and constrained environments.

1.2 Problem Statement

While LLMs display vast application potential on device from smart assistants to personalized content generation they are nonetheless deployed faster than the development of tools for privacy preserving and legally compliant evaluation. Existing privacy risk assessments instead are computationally intensive, confined to cloud based models, or divorced from practical real time use cases. Further complicating matters is this lack of regulatory harmonization across jurisdictional lines, which poses hindrances for developers and system architects attempting to build LLM applications in compliance with the law.

A key challenge is the implementation of adaptive, lightweight, and regulation-aware evaluation mechanisms that can operate within the minuscule resources constrained by mobile and edge devices. In the absence of such measures, organizations risk either deploying AI systems that ultimately fail to achieve mandatory compliance or, worse, risk the erosion of user trust by leaking private data inadvertently.

1.3 Objectives of the Study

This research proposes a new privacy centric framework for evaluating on device LLMs, with the framework's goals as follows:

1. Detecting and mitigating privacy leakage through synthetic data injection and adversarial probing during model inference.
2. Providing transparent and differential audit trails to ensure post inference accountability.
3. Embedding consent aware tracing mechanisms on par with top level privacy statutes.
4. Closing the gulf between the abstruse regulatory requirements and their manifestation in concrete model governance strategies.

Through this, the study aims to contribute to the overarching AI responsibility discourse by proposing a practical solution for LLM deployment that safeguards user privacy and ensures regulatory compliance.

1.4 Structure of the Paper

Section 2 discusses the existing literature on privacy risks and regulatory problems in on-device language model deployment. Section 3 delves into the proposed privacy centric evaluation framework, along with its technical components. Section 4 presents the empirical results of applying the framework to concrete cases. Section 5 expounds on the implications of these empirical results from a regulatory compliance and responsible AI deployment perspective. Finally, Section 6 concludes the works and lays out possible roads for further research.

II. LITERATURE REVIEW

2.1 Account of Privacy Challenges in On Device LLMs

The transition of large language models (LLMs) from cloud centric applications to edge and mobile environments has considerably raised the stakes in user privacy. Unlike in cases of cloud based LLMs that usually have centralized governance, on device models run in isolated, user controlled contexts where traditional governance mechanisms are often absent (Xu et al., 2024). The ensuing change introduced serious privacy concerns, especially when LLMs work on personal data such as voice commands, browsing history, or queries pertaining to health. By decentralizing such configurations, it becomes terribly hard to watch over them to take care of unintentional data retention or leakage (Miranda et al., 2024).

Recent surveys have set out to emphasize the leakage of private information by means of memorization by the model and inference leakage, wherein after multiple users interacting with the model or adversarial prompts, sensitive user inputs inadvertently appear in model outputs (Kibriya et al., 2024; Yao et al., 2024). These threats are further intensified under an on device setup, wherein users expect full control over their own data, while these expectations diverge incredibly from the current infrastructural restraints preventing the extensive deployment of advanced privacy measures such as secure multi-party computation or homomorphic encryption (Yang, 2021).

2.2 Existing Red Teaming and Privacy Auditing Techniques

Red teaming has come to constitute an important sphere in evaluating the potential vulnerabilities of LLMs. It observes simulated attacks for unintended and undesirable behavior of models, data leakage, or even ethical violations. Pujari and Pakina (2023) red teamed phone based LLMs, discovering that adversarial queries could coerce models into the reproduction of private content, even when the training set did not include such data. Alternatively, Shao et al. (2024) proposed PrivacyLens, a method to probe language models for knowledge about data privacy norms in interaction, especially involving personally identifiable information.

To illustrate these evolutions and adoptions of these methods, Table 1 concisely presents the fundamental criteria of red teaming and privacy auditing approaches discussed in the literature.

Table 1: Summary of Red Teaming and Auditing Techniques in LLM Evaluation

Method	Objective	Strengths	Limitations	Source
Red Teaming	Simulated attacks to probe vulnerabilities	Realistic threat simulation	Requires expert human input	Pujari & Pakina (2023)
PrivacyLens	Test model awareness of privacy norms	Focus on behavioral patterns	Limited to pre-defined metrics	Shao et al. (2024)
Synthetic Injection	Inject false data to trace leakage	Effective for inference tracing	May distort model behavior	Zhou et al. (2024)
Consent-Aware Logs	Map consented inputs to outputs	Aligns with legal requirements	Computationally expensive on-device	Woodring et al. (2024)

2.3 Regulatory Landscape and Compliance Challenges

With the proliferation of various AI technologies, the regulators have started promulgating laws for the safe deployment of LLMs. The EU AI Act categorizes AI systems into four levels of risk, with respect to which requirements are placed with regard to documentation, transparency, and human oversight upon high-risk systems. On-device LLMs may be used in the contexts of healthcare or personal finance, which may render them prone to such classifications (Gaurav et al., 2024). The California Consumer Privacy Act (CCPA) and Virginia Consumer Data Protection Act (VCDPA) in the United States require the consent and access rights of people, and algorithmic explainability (Chadwick et al., 2024).

Inconsistent, however, has been regulatory enforcement. Kirk et al. (2024) pointed out how existing regulations usually do not consider fine nuances existing in real-time, personalized model outputs. Standards are also absent for measuring data retention, prompt sensitivity, and post-inference auditability in environments that are resource constrained.

In order to visualize the maturity of regulations around the globe, Figure 1 provides a representation comparing privacy mandates that are relevant to LLM deployment.



Figure 1: Privacy Regulation Comparison for LLMs

Source: Adapted from Gaurav et al. (2024); Chadwick et al. (2024); Díaz-Rodríguez et al. (2023)

2.4 On Device LLM Governance-Technical Gaps

Regulatory mandates speak of transparency and accountability, but somehow translating those calls into actual system designs remains elusive. On device LLMs do not always get access to a remote audit log or a central model that enforces differential privacy (Pandhare, 2024). Table 2 lists some technical possibilities for privacy management, but most need a modification to be actually usable in an on device setting.

Table 2: Technical Methods for Privacy Governance in LLMs

Strategy	On-Device Compatibility	Description	Limitation	Source
Differential Privacy	Low	Adds noise to mask individual contributions	Reduces accuracy	Liu et al. (2023)
Federated Learning	Moderate	Data stays on device; only model updates are shared	High communication overhead	Yang (2021)
Consent-Aware Tracing	Moderate	Tracks user inputs for informed usage logging	Complex for real-time deployment	Woodring et al. (2024)
Personalized Fine-Tuning	High	Customizes models per user profile	Risk of overfitting personal data	Kirk et al. (2023)

2.5 Opportunities to Bridge Policy and Practice

In order to ensure responsible deployment of LLMs on devices, developers have to integrate into the system architecture legal, ethical, and technical principles. According to Miranda et al. (2024), hybrid systems mixing cloud oversight with on device computation are preferable. In addition, Diaz Rodríguez et al. (2023) propose the use of ethical AI maturity models to map development stages to legal requirements. Rivadeneira et al. (2023) propose that consent APIs track in real-time the scope, duration, and terms of data use. The layered architecture for worthy LLM deployment on mobile devices is depicted in Figure 2, integrating these recommendations.



Figure 2: Layered Privacy-Aware LLM Architecture

Source: Based on Rivadeneira et al. (2023); Diaz-Rodríguez et al. (2023)

2.6 Summary of Gaps and Research Direction

A growing literature exists on the evaluation and alignment of LLMs, with fewer studies looking specifically at on-device scenarios, where power constraints, compute constraints, and network access constraints require the emergence of new governance paradigms. Red teaming approaches show promise but can be computationally expensive. Regulators provide good frameworks in theory but lack the real-time enforcement tools of appropriate strength. This literature review reveals a need for adaptable, consent aware, and regulation-aligned mechanisms specific to embedded environments again, this lacuna that this dissertation seeks to fill.

III. FRAMEWORK DESIGN AND METHODOLOGY

3.1 Research Design Approach

This study adopts privacy centric system engineering approach to create a robust, regulation aligned framework for evaluating and deploying on device large language models (LLMs). Grounded in principles of responsible AI, the methodology integrates both qualitative regulatory analysis and quantitative model auditing strategies. The research applies design-science methodology (Peffers et al., 2007) to iteratively build and evaluate a prototype evaluation framework: identifying the problem; setting the solution objectives; designing the artifact; demonstrating the utility of the artifact; and evaluating the effectiveness of the artifact.

The aim is to create a lightly implemented, modular, regulation compliant privacy auditing framework to function on device. The framework leverages existing architectures for red teaming (Shao et al., 2024), scoring for privacy (Pujari & Pakina, 2023), and behavioral inference detection (Kibriya et al., 2024), restricting them to the computational and governance limits of edge devices.

3.2 Evaluation Framework Components

The proposed framework consists of five interlinked modules: Input Monitoring, Consent Mapping, Inference Analysis, Privacy Score Calculation, and a Governance Feedback Loop. Each module functions in real time and abides by compliance principles such as purpose limitation, data minimization, and transparency (Gaurav et al., 2024). Figure 3 depicts the end-to-end architecture of the proposed framework, giving an emphasis on its modular, stackable design.



Figure 3: Modular Architecture of Privacy Evaluation Framework

Source: Author's proposed model, inspired by Pujari & Pakina (2023), Gaurav et al. (2024), and Rivadeneira et al. (2023)

Each module undertakes a separate function:

1. Input Monitoring logs the user interaction and labels the sensitive terms present either through dictionaries or through an ML model.
2. Consent Mapping monitors data flow against stored user permissions and relevant regional laws.
3. Inference Analysis study model outputs to identify either private data being memorized or inferred.
4. Privacy Scoring attaches a quantitative risk score relying on entropy loss, re-identification risk, and user consent violation probability.
5. Governance Feedback Loop Safety with alerts or automated mitigation should violations occur.

3.3 Metrics and Evaluation Criteria

The privacy risk scoring model is one of the core contributions of this work and is designed to provide real-time feedback to users and auditors. The scoring model is a composite of multiple criteria including:

1. Output Sensitivity (based on token entropy),
2. Inference Traceability (via known tags or synthetic insertions),
3. Consent Alignment (percentage of usage of data within users' allowed bounds), and

4. Regulatory Conformance (mapped to GDPR, CCPA, etc.).

Table 3 lists out evaluation criteria used by the scoring engine.

Table 3: Privacy Risk Scoring Metrics

Metric	Description	Weight (%)	Data Source
Output Sensitivity	Measures predictability of tokens in user context	30	Token-level entropy
Consent Alignment	Checks if model respects user data boundaries	25	Consent map logs
Regulatory Match	Maps usage to legal frameworks (e.g., GDPR, CCPA)	20	Policy compliance module
Re-identification Risk	Measures potential to reconstruct user identity	15	Prompt inversion analysis
Usage Transparency	Tracks if usage was logged and disclosed	10	Logging subsystem

Source: Adapted from Zhou et al. (2024), Woodring et al. (2024), and Diaz-Rodríguez et al. (2023)

3.4 Simulation Environment and Implementation

The framework was validated using a prototype implemented on a simulated Android environment with a lightweight LLM (say: LLaMA2 7B quantized with GGUF). Input queries were being sent for synthesis from user profiles coming from varying regulatory jurisdictions (EU, USA, Brazil, and India). Both benign and adversarial prompts were used to test the privacy resilience. Figure 4 shows output entropy plotted against consent violations under different red teaming scenarios.



Figure 4: Entropy vs Consent Violation in Prompt Attacks

Source: Simulated experiment in proposed prototype environment

3.5 Integration with Legal Contexts into the Framework

The principal design objective is regulatory alignment. In order to align such systems, a layer of legal policy abstraction allows developers to bind audit rules dynamically with country-specific regulations. These rules are then mapped up to the level of concrete norms with the compliance mapping matrix (CMM) to ensure that the LLM's behavior follows the regional norm. This abstraction can be useful in the cases of multi-jurisdictional applications such as health bots or finance assistants (Chadwick et al., 2024).Table 4 contains the sample compliance mapping matrix, which is used for the prototype.

Table 4: Compliance Mapping Matrix for Privacy Governance

Region	Consent Required	Right to Explanation	Memory Constraints	Logging Mandate
EU (GDPR)	Yes	Yes	Strict	Yes
USA (CCPA)	Yes	Optional	Moderate	Optional
Brazil (LGPD)	Yes	Yes	Strict	Yes
India (DPDP)	Yes	Yes	Moderate	Yes

Source: Adapted from Gaurav et al. (2024) and Díaz-Rodríguez et al. (2023)

3.6 Summary of Methodology

This section describes the stepwise process that led to the development and testing of a new privacy evaluation framework for on-device LLMs. Combining modular architectural components with legal mappings and empirical simulation, the methodology aims at granting the framework a technical rigor that also lends legal defensibility. The evaluation metrics and compliance mappings create a platform upon which further deployance, testing, and possibly industry acceptance may be built in actual mobile applications.

IV. EXPERIMENTAL RESULTS AND ANALYSIS

4.1 Experimental Setup

In order to validate the privacy evaluation framework proposed for on-device LLMs, a battery of controlled experiments was carried out using a simulation of the mobile edge environment. The simulation consisted of a quantized LLaMA-2 7B GGUF version running on the device-mirroring environment emulating an Android system with a privacy sandbox. Synthetic and real-world prompts were then subjected to testing in a wide variety of privacy-sensitive contexts such as health inquiries, financial data, and political opinions).

The experiments tested three primary aspects:

1. How capable the framework is at detecting privacy violations,
2. How accurate are the privacy risk scores it generates,
3. The framework's compliance alignment under different jurisdictions.

While testing, model outputs were logged and scored in real-time with the internal Privacy Risk Scoring Engine (PRSE) described in Section 3.3. Comparative evaluations were done under four prompt categories: benign, synthetic PII, adversarial membership inference, and location tracking scenarios.

4.2 Privacy Risk Distribution across Prompt Types

The framework then assigns a privacy risk score to each output between 0 and 1, with an increasing number implying a higher probability of privacy violation. A total of 1,000 interactions between prompt and output were analyzed. The results exhibited clear significance levels to separate categories of prompts. Figure 5 below shows the distribution of average privacy risk scores for different prompt types.



Figure 5: Average Privacy Risk Score by Prompt Type

Source: Author's simulation based on 1,000 prompt evaluations in the prototype environment.

The results showed membership inference attacks with the highest ratings at an average risk score of 0.68, reinforcing the notion of its sensitivity in literature (Carlini et al., 2021). Even synthetic PII prompts were scored with a significantly higher score than benign ones, providing evidence that the framework can dynamically distinguish based on context-based risk.

4.3 Detection Precision and Recall Analysis

The risk scoring engine's precision was examined by taking labeled ground truth outputs and comparing them against the set of outputs that were flagged as high-risk. Outputs were considered risky at a threshold of 0.5. Performance was then measured in terms of standard precision, recall, and F1-score. Detection performance for the three prompt categories (excluding benign) is summarized in Table 5.

Table 5: Precision and Recall of Privacy Violation Detection

Prompt Type	Precision	Recall	F1-Score
Synthetic PII	0.84	0.72	0.77
Membership Attack	0.89	0.78	0.83
Location Tracking	0.81	0.75	0.78

Source: Computed from simulation logs using 800 labeled outputs.

These results indicate high precision and acceptable recall, showing that the framework is more conservative in labeling outputs risky a design choice aligned with responsible AI practices (Zhou et al., 2024). The detection model may miss some subtle violations (lower recall), but rarely misclassifies benign outputs (high precision).

4.4 Evaluation for Legal Compliance Alignment

The highest domain considered here is to ensure maximum enforcement of local, regional, or international legal provisions. The prompt-output interactions were filtered in simulation through regionalistic legal perspectives: GDPR (EU), CCPA (USA), LGPD (Brazil), and DPDP (India). The compliance mapping engine performs a cross-check on outputs concerning consent requirements, memory restrictions, logging obligations. The Table 6 summarizes the number of counts of the non-compliant outputs detected under each jurisdiction.

Table 6: Privacy Compliance Violations by Jurisdiction

Regulation	Violations Detected	% of Total Outputs	Common Issue
GDPR (EU)	78	7.8%	Inference beyond consent scope
CCPA (USA)	32	3.2%	Insufficient transparency
LGPD (Brazil)	61	6.1%	Memory retention violations
DPDP (India)	54	5.4%	Absence of justification log

Source: Derived from compliance mapping module using 1,000 prompt evaluations.

Due to its stringent consent enforcement and inference restrictions, the most violations under consideration fell within the domain of the GDPR. Such findings gave rise to the need for contextual jurisdictional filtering while affirming the significance of adaptive legal mapping in the deployment of mobile LLMs (Gaurav et al., 2024).

4.5 Output Diversity and Sensitivity Correlation

The final experiment explored whether the degree of diversity of the LLM output (calculated by means of a type-token ratio and entropy) is correlated with the privacy sensitivity. More precise outputs sometimes offer greater detail regarding an individual. Figure 6 presents an overview of output entropy plotted against the risk score across all considered prompts.



Figure 6: Correlation between Output Entropy and Privacy Risk

Source: Author's regression simulation using synthetic output sample.

Nonlinearity is demonstrated by the scatter plot: less entropy outputs tend to be associated with higher privacy risk scores (from memorization or overconfidence) while extremely high entropy outputs sometimes go up to the privacy scores due to the difficulties of measuring unpredictability in sensitive domains (Shokri et al., 2021).

4.6 Summary of Findings

The experimental analysis suggests that the proposed framework is capable in detecting privacy risks, scoring outputs accurately, and insisting on jurisdictional compliance; also, this supports arguments on the need for real-time metrics, red teaming protocols, and dynamic legal filters in any on-device LLM deployment. Lastly, the statistical relationship between output entropy and privacy scores opens a new avenue for interpretability research.

V. DISCUSSION AND IMPLICATIONS

5.1 Interpretation of Privacy Evaluation Results

The experimental results from the prior section paint a nuanced picture of the on-device language models under evaluation within a systematically organized privacy-oriented framework. One of the most significant findings was the framework's ability to discriminate among different types of prompts with respect to associated privacy risks. As shown in Figure 5, membership inference attacks consistently yield higher risk scores, thereby corroborating earlier concerns about LLMs unintentionally memorizing sensitive training data (Carlini et al., 2021). This intensifies the call for robust memorization checks not only at the model pretraining stage but also during deployment.

Similarly, the jurisdictional compliance violations captured in Table 6 reflect the intricacies in aligning AI outputs to disparate regional statutes such as the GDPR, CCPA, and LGPD, since these laws differ in their requirements for data minimization, consent, and retention policies. The very capability of the framework to pick up these distinctions in real time should thus be welcomed by developers and auditors alike. Interestingly, outputs deemed compliant under one regulatory regime were usually illegal under another, highlighting the necessity of flexible and context-sensitive compliance strategies (Gaurav et al., 2024).

5.2 Practical Implications for On-Device Deployment

LLM deployment on edge devices (such as smartphones) presents novel challenges and opportunities. Privacy-wise, local computation seems beneficial-the data remains on the device, reducing the exposure to centralized data leaks. However, as demonstrated by our framework, privacy risks are not simply eliminated by moving the model to the device. On-device LLMs still output results that violate data protection principles, especially when they are fine-tuned on or exposed to sensitive prompts. Table 7 offers a comparative examination of the privacy trade-offs between cloud-based and on-device deployment of LLMs.

Table 7: Comparative Privacy Implications: Cloud vs On-Device LLMs

Factor	Cloud LLMs	On-Device LLMs
Data Transit Risk	High	Low
Local Control	Low	High
Update Flexibility	High	Limited
Real-Time Red Teaming	Centralized	Local or Hybrid
Regulatory Adaptation	Region-aware servers	User-dependent filtering

Source: Adapted from Bandy et al. (2022) and modified based on simulation insights.

While on-device systems enhance local control and reduce transit risks, they often lack real-time updates and centralized red teaming capability, leaving room for local enforcement engines such as the one created in this paper.

5.3 Policy and Governance Issues

Viewing it from governance, it supports the decentralized, adaptive governance at a wider level of AI. The set framework allows for continuous, localized monitoring and enforcement instead of depending on traditional post-deployment audits or manual red teaming. This echoes emerging trends in regulatory AI which are shifting towards context-aware safeguards and real-time audits (OECD, 2023). Figure 7 below shows how the framework interfaces with the multi-layered governance architecture.



Figure 7: Integrated Privacy Governance for On-Device LLMs

Source: Author's conceptual model inspired by Gasser & Almeida (2023).

This model of layers emphasizes the fact that privacy cannot just be guaranteed at the model layer. Rather, it requires an orchestrated interaction between applications design, legal filters for service deployment, monitoring of model behavior, and a transparent user control interface. The architecture sets forth the means to harmonize regulation without stifling innovation.

5.4 Dangers of Over-Filtering and Lost Utility

One potential danger of strong privacy filtering mechanisms is utility degradation, where over-cautious risk scoring thresholds may block beneficial outputs. This is especially the case for domains where creativity and nuances matter, like mental health, legal advice, or financial planning.

To study this trade-off, the authors conducted a utility-retention analysis comparing model outputs before and after privacy filtering. Outputs were examined for helpfulness on a 0-to-10 scale by three human annotators, adapting OpenAI eval criteria. Figure 8 displays a drop or rise in average utility scores before and after filtering.



Figure 8: Output Utility Score Before and After Privacy Filtering

Source: Evaluation conducted on 100 responses using a modified OpenAI eval scale.

An average utility loss of 0.9 is observed, with it being especially pronounced across health and legal queries. This, then, poses pressing questions: How should one weigh safety versus usefulness or could risk scores even be personalized or contextually adapted so as to minimize extraneous filtering? (Leins et al., 2023).

5.5 Ethical and Social Implications

There are, of course, even further-than-technical, beyond-legal ethical implications whenever one speaks of privacy-aware on-device LLMs. Privacy-respecting personalized LLMs can, essentially, empower users from underserved regions by allowing them to access financial tools and health support, as well as localized education, completely free of surveillance fears. Still, the dual-use risk remains, with bad actors trying to circumvent local filters or jailbreaking models for all intents.

Consequently, ethics must inform the design architecture, transparency, open auditing, and clear user feedback loops included. Collaboration with civil society and legal experts during the design phases shall ensure that such frameworks incorporate community norms and not just legal norms (Crawford, 2021).

5.6 Summary of Implications

Thus, one may summarize implications as: In general, our results suggest that it is possible for on-device language models to be responsibly deployed if, and only if, there exist privacy-preserving evaluation frameworks within a runtime environment. Such frameworks should be a balanced tradeoff between privacy enforcement and usefulness of the model and keep pace with changing regulations, all from on-the-fly operation on constrained devices. Evolving coexistence of legal, technical, and ethical considerations would thus guarantee generative AI deployment in the wild on personal devices from both a safe and socially acceptable standpoint.

VI. CONCLUSION AND FUTURE DIRECTIONS

Rapid advancements in on-device large language models bring unique opportunities and challenges that threaten privacy, ethics, and regulatory set-ups. To this end, the study proposes and in its validation has established a complete privacy-centric methodology for assessing how on-device LLMs behave versus privacy threats and jurisdiction regulations. Implemented in a multi-layer setting, this framework analyzes outputs through red-teaming, risk scoring, and real-time filtering methods to identify potentially harmful or non-compliant content, which could be used by both developers and regulators to spawn responsible AI technologies for decentralized environments.

The results show that privacy risks still pervade on-device LLMs despite their offline execution, considering that their physical data locality alone does not ensure compliance or user safety (Gaurav et al., 2024; Miranda et al., 2024). Membership inference, data leakage, and jurisdictional non-compliance may all be ever-looming threats that require ingenious and intelligent monitoring integrations housed within the device ecosystem. This coincides with current works emphasizing the necessity for context-aware, user-centered privacy protections which can vary depending on an evolving legal framework or user preferences (Zhou et al., 2024; Rivadeneira et al., 2023).

Additionally, another research finding is that there remains an inherent struggle between ensuring stringent privacy provisions and saving the utility and granularity of an LLM output. Heavy filtering will reduce the markedly helpful service the model offers, particularly in nuanced areas like health care and legal advice. Thereby, future research could focus on adaptive filtering thresholds and personalized risk scoring that maintain the balance between safety and user convenience, possibly based on reinforcement learning or user feedback loops to further optimize this balance continually (Kirk et al., 2024; Chen et al., 2024). Place the trustworthiness and user engagement in far more stands ahead than regulatory compliance.

According to governance terms, this research stresses a paradigm shift that paves the way for decentralized and continuous privacy supervision. The layered governance architecture presented hereallows for localized enforcement and maintains alignment with global regulatory principles, representing a practicable model for the future of AI oversight in fractured legal domains (Díaz-Rodríguez et al., 2023; Gaurav et al., 2024). Promoting transparency in reporting, auditing, and stakeholder collaboration shall further fortify the accountability and social license of on-device LLM deployment (Radanliev et al., 2024; Mylrea & Robinson, 2023).

Several key directions unfold in the distance for further inquiry. First, with the continuous diversification of AI capabilities, the expansion of the evaluation framework to apply to multimodal models that engage with images, audio, and text will be necessary (Shen et al., 2023). Second, thirdly, the integration of federated learning techniques might improve guarantees of privacy by distributed training without central data aggregation, which perfectly complements the on-device execution paradigm (Yang, 2021). Long-term considerations on user behavior, privacy perception, and social impacts of personalized on-device AI are in turn required to lay down the foundations upon which to build ethical design and policymaking (Williamson & Prybutok, 2024; Obradovich et al., 2024).

In summary, the responsible deployment of on-device large language models is an ambitious goal yet remains within reach. This research lays a foundation for a framework to tackle urgent privacy and regulatory challenges alongside practical utility and ethical integrity issues. The growing integration of AI systems into ordinary devices will sharpen the insights and tools developed here to assist in realizing a future where generative AI respects and transparently empowers its users.

REFERENCES

[1] Gaurav, A., Gupta, B. B., Wu, J., & Chaurasia, P. (2024). Regulatory and Policy Considerations for Large Language Models: Frameworks, Implications, and Future Directions. In *Challenges in Large Language Model Development and AI Ethics* (pp. 212-238). IGI Global.

[2] Zhou, S., Zhou, Z., Wang, C., Liang, Y., Wang, L., Zhang, J., ... & Lv, C. (2024). A User-Centered Framework for Data Privacy Protection Using Large Language Models and Attention Mechanisms. *Applied Sciences*, *14*(15), 6824.

[3] Pujari, Mangesh & Pakina, Anil Kumar. (2023). Balancing Innovation and Privacy: A Red Teaming Approach to Evaluating Phone-Based Large Language Models under AI Privacy Regulations. International Journal Science and Technology. 2. 10.56127/ijst.v2i3.1956.

[4] Woodring, J., Perez, K., & Ali-Gombe, A. (2024). Enhancing privacy policy comprehension through privacify: A user-centric approach using advanced language models. *Computers & Security*, *145*, 103997.

[5] Shao, Y., Li, T., Shi, W., Liu, Y., & Yang, D. (2024). Privacylens: Evaluating privacy norm awareness of language models in action. *arXiv preprint arXiv:2409.00138*.

[6] Kibriya, H., Khan, W. Z., Siddiqa, A., & Khan, M. K. (2024). Privacy issues in large language models: a survey. *Computers and Electrical Engineering*, *120*, 109698.

[7] Kirk, H. R., Vidgen, B., Röttger, P., & Hale, S. A. (2024). The benefits, risks and bounds of personalizing the alignment of large language models to individuals. *Nature Machine Intelligence*, *6*(4), 383-392.

[8] Chadwick, R., Blundell, S., & Prendergast, E. (2024). Assessments of the privacy compliance in commercial large language models.

[9] Kirk, H. R., Vidgen, B., Röttger, P., & Hale, S. A. (2023). Personalisation within bounds: A risk taxonomy and policy framework for the alignment of large language models with personalised feedback. *arXiv preprint arXiv:2303.05453*.

[10] Radanliev, P., Santos, O., Brandon-Jones, A., & Joinson, A. (2024). Ethics and responsible AI deployment. *Frontiers in Artificial Intelligence*, *7*, 1377011.

[11] Yang, Q. (2021). Toward responsible ai: An overview of federated learning for user-centered privacy-preserving computing. *ACM Transactions on Interactive Intelligent Systems (TiiS)*, *11*(3-4), 1-22.

[12] Shen, T., Jin, R., Huang, Y., Liu, C., Dong, W., Guo, Z., ... & Xiong, D. (2023). Large language model alignment: A survey. *arXiv preprint arXiv:2309.15025*.

[13] Xu, J., Li, Z., Chen, W., Wang, Q., Gao, X., Cai, Q., & Ling, Z. (2024). On-device language models: A comprehensive review. *arXiv preprint arXiv:2409.00088*.

[14] Miranda, M., Ruzzetti, E. S., Santilli, A., Zanzotto, F. M., Bratières, S., & Rodolà, E. (2024). Preserving privacy in large language models: A survey on current threats and solutions. *arXiv preprint arXiv:2408.05212*.

[15] Tarkoma, S., Morabito, R., & Sauvola, J. (2023). AI-native interconnect framework for integration of large language model technologies in 6G systems. *arXiv preprint arXiv:2311.05842*.

[16] Rivadeneira, J. E., Silva, J. S., Colomo-Palacios, R., Rodrigues, A., & Boavida, F. (2023). User-centric privacy preserving models for a new era of the Internet of Things. *Journal of Network and Computer Applications*, *217*, 103695.

[17] Mylrea, M., & Robinson, N. (2023). Artificial Intelligence (AI) trust framework and maturity model: applying an entropy lens to improve security, privacy, and ethical AI. *Entropy*, *25*(10), 1429.

[18] Chen, J., Liu, Z., Huang, X., Wu, C., Liu, Q., Jiang, G., ... & Chen, E. (2024). When large language models meet personalization: Perspectives of challenges and opportunities. *World Wide Web*, *27*(4), 42.

[19] Malode, V. M. (2024). *Benchmarking public large language model* (Doctoral dissertation, Technische Hochschule Ingolstadt).

[20] Pandhare, H. V. (2024). Evaluating Large Language Models: Frameworks and Methodologies for AI/ML System Testing. *International Journal of Scientific Research and Management (IJSRM)*, *12*(09), 1467-1486.

[21] Gupta, B. B., Gaurav, A., Arya, V., Alhalabi, W., Alsalman, D., & Vijayakumar, P. (2024). Enhancing user prompt confidentiality in Large Language Models through advanced differential encryption. *Computers and Electrical Engineering*, *116*, 109215.

[22] Williamson, S. M., & Prybutok, V. (2024). Balancing privacy and progress: a review of privacy challenges, systemic oversight, and patient perceptions in AI-driven healthcare. *Applied Sciences*, *14*(2), 675.

[23] Pujari, T., Goel, A., & Sharma, A. (2024). Ensuring responsible AI: The role of supervised fine-tuning (SFT) in upholding integrity and privacy regulations. *International Journal Science and Technology*, *3*(3), 46-55.

[24] Liu, Y., Han, T., Ma, S., Zhang, J., Yang, Y., Tian, J., ... & Ge, B. (2023). Summary of chatgpt-related research and perspective towards the future of large language models. *Meta-radiology*, *1*(2), 100017.

[25] Yao, Y., Duan, J., Xu, K., Cai, Y., Sun, Z., & Zhang, Y. (2024). A survey on large language model (llm) security and privacy: The good, the bad, and the ugly. *High-Confidence Computing*, 100211.

[26] Ferrara, E. (2023). Should chatgpt be biased? challenges and risks of bias in large language models. *arXiv preprint arXiv:2304.03738*.

[27] Khowaja, S. A., Khuwaja, P., Dev, K., Wang, W., & Nkenyereye, L. (2024). Chatgpt needs spade (sustainability, privacy, digital divide, and ethics) evaluation: A review. *Cognitive Computation*, *16*(5), 2528-2550.

[28] Obradovich, N., Khalsa, S. S., Khan, W. U., Suh, J., Perlis, R. H., Ajilore, O., & Paulus, M. P. (2024). Opportunities and risks of large language models in psychiatry. *NPP—Digital Psychiatry and Neuroscience*, *2*(1), 8.

[29] Díaz-Rodríguez, N., Del Ser, J., Coeckelbergh, M., de Prado, M. L., Herrera-Viedma, E., & Herrera, F. (2023). Connecting the dots in trustworthy Artificial Intelligence: From AI

principles, ethics, and key requirements to responsible AI systems and regulation. *Information Fusion*, *99*, 101896.

[30] Shen, H., Knearem, T., Ghosh, R., Alkiek, K., Krishna, K., Liu, Y., ... & Jurgens, D. (2024). Towards bidirectional human-ai alignment: A systematic review for clarifications, framework, and future directions. *arXiv preprint arXiv:2406.09264*.