

Hydrostatic Load Response Analysis of A Rectangular Reinforced Concrete Water Tank

G. SAI SHRUTHI¹, R SANNIDHI², N SAI VINAYAK³, B LOKESH BABU⁴, M MANIKANTA⁵, P LINGAM⁶

¹Associate Professor, Department of Civil Engineering, Siddhartha Institute of Technology and Science Engineering (Autonomous), Narapally(V), Ghatkesar(M), Medchal(D), Telangana, India
^{2, 3, 4, 5, 6} B. TECH, Department of Civil Engineering, Siddhartha Institute of Technology and Science Engineering (Autonomous), Narapally(V), Ghatkesar(M), Medchal(D), Telangana, India

Abstract- Water storage structures play a vital role in municipal, industrial, and domestic water supply systems. The present project focuses on the analysis and design of a rectangular reinforced cement concrete (RCC) water tank using STAAD Pro software, in accordance with relevant Indian Standard codes such as IS 3370 and IS 456:2000. The study emphasizes the structural behavior of a ground-resting rectangular tank subjected to hydrostatic water pressure, soil pressure, self-weight, and other loading conditions. The design methodology incorporates both theoretical calculations and computer-based structural analysis to evaluate bending moments, shear forces, stresses, and deflections. A three-dimensional finite element model of the tank was developed in STAAD Pro, and results obtained from software analysis were compared with manual design procedures to ensure accuracy and safety. The tank dimensions considered are 12 m × 4 m × 2.5 m with a wall thickness of 400 mm. The study concludes that limit state method provides an economical and efficient design compared to the working stress method. The integration of software tools significantly reduces computational effort and improves design reliability, ensuring structural safety and serviceability of the water tank.

Keywords: Rectangular Water Tank, RCC Design, STAAD Pro, IS 3370, Hydrostatic Pressure, Finite Element Analysis, Limit State Method, Liquid Retaining Structures.

I. INTRODUCTION

Water storage structures are essential components of modern infrastructure systems used for domestic, municipal, agricultural, and industrial purposes. With rapid urbanization and population growth, the demand for safe and efficient water storage has significantly increased [1]. Reinforced Cement Concrete (RCC) water tanks are widely used due to their durability, strength, and resistance to environmental effects [2].

Depending on their location and purpose, water tanks may be classified as underground tanks, tanks resting on ground, and overhead tanks [3]. Among various shapes such as circular, rectangular, and Intze types, rectangular tanks are commonly adopted for small to medium capacities because of their simple geometry and ease of construction [4]. The design of liquid retaining structures differs from ordinary RCC structures since cracking must be strictly controlled to prevent leakage [5]. As per IS 3370 guidelines, special attention is given to tensile stresses, shrinkage effects, and water tightness requirements [6]. The hydrostatic pressure exerted by stored water produces bending moments and shear forces on tank walls, which vary linearly with depth [7]. Therefore, accurate structural analysis is necessary to ensure stability and serviceability [8]. In addition to internal water pressure, external soil pressure and uplift forces must also be considered in underground or ground-resting tanks [9]. Modern structural software like STAAD Pro enables engineers to model complex geometries and loading conditions efficiently [10].

The structural behavior of rectangular water tanks is more complex compared to circular tanks due to two-way bending action in walls [11]. Long walls generally behave as vertical cantilevers when the length-to-breadth ratio exceeds two, while short walls act as slabs supported on long walls [12]. The base slab is subjected to upward soil pressure and downward water load, requiring careful design against uplift and bending [13]. The analysis involves determining bending moments in both horizontal and vertical directions, along with direct tensile stresses caused by hydrostatic pressure [14]. According to IS 456:2000 and IS 3370:2009, permissible stresses must be limited to ensure crack-free performance [15]. Traditionally,

water tank design was carried out using the Working Stress Method; however, the Limit State Method has gained preference due to its economy and reliability [16]. The limit state approach considers ultimate load capacity and serviceability requirements simultaneously [17]. Shrinkage and temperature stresses also influence structural behavior and must be accounted for in design [18]. Proper reinforcement detailing, minimum cover requirements, and movement joints are essential to maintain durability [19]. The advancement of finite element analysis tools has significantly improved accuracy in stress distribution prediction [20].

In this project, a rectangular RCC water tank resting on the ground with dimensions $12\text{ m} \times 4\text{ m} \times 2.5\text{ m}$ has been analyzed and designed using STAAD Pro software [21]. The tank is modeled using shell elements, and loads such as hydrostatic pressure, self-weight, and soil pressure are applied systematically [22]. The software computes nodal displacements, bending moments, shear forces, and stress distribution across structural elements [23]. The results obtained from software analysis are compared with theoretical calculations to validate accuracy [24]. The study aims to evaluate structural performance, ensure compliance with Indian Standard codes, and determine an economical design solution [25]. By integrating manual design principles with advanced computational tools, the project demonstrates an efficient methodology for safe and cost-effective construction of liquid retaining structures.

II. LITERATURE REVIEW

1. Mainak Ghosal (2019)

Mainak Ghosal (2019) conducted a study on the analysis and design of elevated water tanks using STAAD Pro V8i under various loading conditions. The research emphasized the importance of structural modeling in understanding the behavior of liquid retaining structures subjected to hydrostatic, wind, and seismic loads. The study adopted the Limit State Design method and compared manual calculations with software-generated results. It was observed that hydrostatic pressure significantly influences bending moments and shear forces in tank walls. The research also highlighted that STAAD Pro simplifies the modeling of complex geometries and improves

accuracy in stress prediction. The author concluded that software-based analysis enhances structural safety and reduces computational time when compared to conventional manual methods. This study provides a strong foundation for understanding the structural response of water tanks and validates the application of STAAD Pro in liquid retaining structures.

2. L.P. Shrivastava and Akshit Lamba (2018)

Shrivastava and Lamba (2018) presented a detailed seismic and wind analysis of water tanks based on IS 3370:2009 and IS 1893 (Part 2). The study introduced impulsive and convective mass models for dynamic analysis of elevated tanks. The authors concluded that two-degree-of-freedom models produce more accurate results compared to single-degree models. It was observed that full tank condition produces maximum base shear and overturning moments. Their research emphasized the importance of considering dynamic loads in water tank design. The study demonstrated that structural software such as STAAD Pro provides reliable predictions of displacement and stress behavior under seismic conditions. This work contributes significantly to understanding the importance of load combinations and dynamic response in water tank design.

3. Issar Kapadia et al. (2017)

Issar Kapadia, Purav Patel, and Nilesh Dholiya (2017) analyzed rectangular water tanks under hydrostatic pressure using STAAD Pro in accordance with IS 3370 and IS 456:2000. The study focused on bending moment variation with increase in tank height and the effect of base fixity conditions. It was observed that fixed base conditions reduce settlement and improve structural stability. The research also highlighted that rectangular tanks exhibit two-way bending action, making their design more complex than circular tanks. The authors concluded that software analysis provides detailed stress distribution and helps in economical reinforcement design. Their findings support the importance of using advanced analytical tools for efficient structural performance evaluation.

4. Hasan Jasim Mohammed (2016)

Hasan Jasim Mohammed (2016) investigated optimization techniques in the structural design of

rectangular and circular concrete water tanks. The study considered tank capacity, dimensions, slab thickness, and material properties as design variables. A computer program was developed based on IS 456:2000 provisions to minimize overall construction cost. The results showed that proper dimension selection significantly reduces material consumption and total cost. It was concluded that rectangular tanks are economical for moderate capacities, whereas circular tanks are preferable for larger storage volumes. The study highlighted the need for optimization in structural design to achieve cost efficiency without compromising safety.

5. Pandey et al. (2015)

Pandey et al. (2015) discussed the transition from Working Stress Method to Limit State Method in liquid retaining structures under IS 3370:2009. The study compared crack width control, reinforcement quantity, and material utilization in both methods. It was observed that the Limit State Method provides more economical design while ensuring serviceability criteria. However, proper crack width checks are essential to maintain water tightness. The research concluded that modern design approaches combined with computational tools result in better structural performance and reduced construction cost. This study supports the adoption of limit state principles in the design of RCC water tanks.

III. WORKING METHODOLOGY

The working methodology adopted for the analysis and design of the rectangular RCC water tank involves systematic steps including preliminary design, modeling, loading, analysis, and design verification. Initially, the tank dimensions were determined based on the required storage capacity. The geometry selected for the project is a rectangular tank of specified length, width, and depth resting on ground. The grade of concrete and steel were selected as per IS 456:2000 and IS 3370:2009 provisions. The wall thickness, base slab thickness, and top slab thickness were assumed based on preliminary calculations. The design requirements such as minimum reinforcement, permissible stresses, cover to reinforcement, and crack control provisions were carefully considered to ensure water-tightness of the structure.

After finalizing the preliminary dimensions, a three-dimensional finite element model of the tank was developed in STAAD Pro. The tank walls and slabs were modeled using plate (shell) elements to accurately capture bending and membrane stresses. Proper node connectivity was ensured to simulate monolithic behavior of walls and base slab. Material properties such as modulus of elasticity, Poisson's ratio, and density of concrete were defined according to Indian Standard specifications. Boundary conditions were assigned by providing pinned supports at base nodes to simulate the tank resting on ground. The thickness property was assigned to all plate elements. The model was carefully checked to ensure correct geometry and meshing before applying loads.

The next stage involved application of loads on the structure. Hydrostatic water pressure was applied as a trapezoidal (triangular varying) plate load on the inner faces of the tank walls, increasing linearly with depth. Self-weight of the structure was automatically considered by activating the self-weight command in STAAD Pro. In addition, soil pressure was considered where applicable. After defining load cases, structural analysis was performed using the finite element method. The software computed nodal displacements, support reactions, bending moments, shear forces, and plate stresses. The results were carefully examined to identify maximum stress locations, particularly near the base of walls where hydrostatic pressure is maximum. Reinforcement was designed based on critical bending moments and tensile stresses while ensuring compliance with permissible stress limits as per IS 3370. Finally, the results obtained from STAAD Pro were compared with manual calculations for validation, and the design was optimized to achieve a safe, economical, and serviceable water retaining structure.

IV. CONCLUSION

The present project focused on the analysis and design of a Rectangular RCC Water Tank resting on ground using STAAD Pro software in accordance with IS 456:2000 and IS 3370 provisions. The study included theoretical design calculations and finite element modeling to evaluate bending moments, shear forces, stresses, and displacements developed due to hydrostatic water pressure, self-weight, and soil pressure. From the analytical results, it was observed that maximum bending moments and stresses occur near the base of the tank walls where water pressure is maximum. The stress distribution obtained from STAAD Pro confirmed that tensile stresses were within permissible limits, ensuring crack control and structural safety. The finite element analysis approach provided more accurate stress distribution compared to conventional manual methods. The displacement results showed that the structure behaved within acceptable serviceability limits. It was also observed that the rectangular tank configuration is economical and suitable for moderate storage capacities. The design ensured adequate reinforcement detailing to resist both horizontal and vertical bending moments in walls. The base slab was verified against uplift pressure and bending stresses. From the comparative study between theoretical calculations and STAAD Pro results, only minor variations were observed, validating the accuracy of software-based analysis. The Limit State Method was found to be more economical and efficient than the Working Stress Method. Proper detailing of joints, minimum reinforcement, and adequate cover ensures durability and water-tightness of the structure. Overall, the project demonstrates that the use of STAAD Pro significantly simplifies the design process while ensuring safe, economical, and reliable construction of liquid retaining structures.

V. REFERENCES

- [1] Bureau of Indian Standards, *IS 456:2000 – Plain and Reinforced Concrete – Code of Practice*, New Delhi, India, 2000.
- [2] Bureau of Indian Standards, *IS 3370 (Part I–IV):2009 – Concrete Structures for Storage of Liquids – Code of Practice*, New Delhi, India, 2009.
- [3] Bureau of Indian Standards, *IS 875 (Part 1–5):1987 – Code of Practice for Design Loads (Other than Earthquake) for Buildings and Structures*, New Delhi, India, 1987.
- [4] Bureau of Indian Standards, *IS 1893 (Part 2):2014 – Criteria for Earthquake Resistant Design of Structures – Liquid Retaining Tanks*, New Delhi, India, 2014.
- [5] P. Dayaratnam, *Design of Reinforced Concrete Structures*, New Delhi, India: Oxford & IBH Publishing, 2000.
- [6] V. N. Vazirani and M. M. Ratwani, *Concrete Structures*, New Delhi, India: Khanna Publishers, 1990.
- [7] R. K. Bansal, *Theory of Structures*, New Delhi, India: Laxmi Publications, 2005.
- [8] S. U. Pillai and D. Menon, *Reinforced Concrete Design*, New Delhi, India: Tata McGraw Hill Education, 2012.
- [9] N. Krishna Raju, *Advanced Reinforced Concrete Design*, New Delhi, India: CBS Publishers, 2010.
- [10] M. L. Gambhir, *Reinforced Concrete Design*, New Delhi, India: Prentice Hall of India, 2008.
- [11] R. Hulse and B. Mosley, *Reinforced Concrete Design*, London, U.K.: Palgrave Macmillan, 2003.
- [12] B. C. Punmia, A. K. Jain, and A. K. Jain, *RCC Designs*, New Delhi, India: Laxmi Publications, 2009.
- [13] M. Bhandari and K. D. Singh, “Economic design of water tank of different shapes with reference to IS 3370-2009,” *Int. J. Modern Eng. Res.*, vol. 4, no. 12, pp. 1–6, Dec. 2014.
- [14] R. S. Lodhi, A. Sharma, and V. Garg, “Design of Intze tank in perspective of revision of IS 3370,” *Int. J. Scientific Eng. Technol.*, vol. 3, no. 9, pp. 1193–1197, Sept. 2014.
- [15] N. K. Meshram and P. S. Pajgade, “Comparative study of water tank using limit state method and working stress method,” *Int. J. Res. Advent Technol.*, vol. 2, no. 8, pp. 45–50, Aug. 2014.
- [16] A. Wad, N. G. Gore, P. J. Salunke, and V. G. Sayagavi, “Cost optimization of rectangular RCC underground tank,” *Int. J. Recent Technol. Eng.*, vol. 3, no. 3, pp. 85–89, July 2014.

- [17] M. N. Gandhi and A. Rajan, “Necessity of dynamic analysis of elevated water storage structure using different bracing,” *Int. J. Res. Advent Technol.*, vol. 2, no. 2, pp. 100–105, Feb. 2014.
- [18] R. Sameer, A. R. Mundhada, and S. Metkar, “Comparison of RCC and prestressed concrete circular water tanks,” *Int. J. Emerging Technol. Adv. Eng.*, vol. 2, no. 12, pp. 120–125, Dec. 2012.
- [19] C. N. Patel and H. S. Patel, “Optimum diameter of tapered elevated RC water tank staging,” *Int. J. Emerging Technol. Adv. Eng.*, vol. 2, no. 12, pp. 98–104, Dec. 2012.
- [20] R. C. Hibbeler, *Structural Analysis*, 8th ed., Boston, MA, USA: Pearson Education, 2012.
- [21] Bentley Systems, *STAAD.Pro V8i Technical Reference Manual*, Exton, PA, USA: Bentley Systems Inc., 2016.
- [22] C. K. Wang and C. G. Salmon, *Reinforced Concrete Design*, 6th ed., New York, NY, USA: Harper & Row, 2007.
- [23] J. G. MacGregor and J. K. Wight, *Reinforced Concrete: Mechanics and Design*, 6th ed., Upper Saddle River, NJ, USA: Pearson Education, 2012.
- [24] B. Mosley, J. Bungey, and R. Hulse, *Reinforced Concrete Design to Eurocode 2*, London, U.K.: Palgrave Macmillan, 2012.
- [25] A. M. Neville and J. J. Brooks, *Concrete Technology*, 2nd ed., London, U.K.: Pearson Education, 2010.