

ARCHITECTURE

Thermal Performance and Cooling Mechanisms of Thatch Roofs in Nigerian Traditional Architecture

Ochi Ejimofor¹, Chukwuma Anya²

¹Department of Architecture, Faculty of Environmental Studies, Abia State University, Uturu, Abia State, Nigeria

²Department of Architectural Technology, School of Environmental and Design Technology, Ogbonnaya Onu Polytechnic, Aba, Abia State, Nigeria

Published October 2026

Abstract

Contemporary architecture in Nigeria has largely abandoned indigenous building typologies in favor of Western-derived, energy-intensive designs reliant on reinforced concrete and corrugated metal sheets. This shift has resulted in severe indoor thermal discomfort, necessitating massive energy consumption for mechanical cooling. This paper provides a comprehensive thermodynamic and architectural analysis of the cooling efficacy of thatch roofs combined with mud walls in Nigerian traditional architecture. By examining the physical properties of organic materials, structural geometry, and aerodynamic ventilation, this study elucidates how indigenous builders achieved optimum indoor comfort under tropical conditions. Comparative data analysis indicates that thatch-roofed mud structures maintain significantly lower interior temperatures and higher thermal damping compared to modern counterparts, offering critical lessons for sustainable, low-energy tropical architecture.

Keywords: thatch roof; mud house; thermal comfort; traditional architecture; Nigeria; high-pitched roof

1 Introduction

Nigeria spans multiple climatic zones, ranging from the tropical wet-and-dry (Aw) in the central and southern regions to the semi-arid Sahelian (BSh) climate in the extreme north. Across these regions, ambient temperatures frequently exceed 35°C with high relative humidity. Historically, indigenous populations developed sophisticated vernacular architectural systems optimized for these climatic stressors without the aid of mechanical HVAC systems.

Central to this indigenous thermal control system is the synergy between **mud (earth) walls** and **thatch roofs**. While earth walls provide massive thermal inertia, the thatch roof acts as a dynamic thermal regulator. Despite its proven performance, thatch is frequently mischaracterized as a symbol of poverty, leading to its systematic replacement by corrugated galvanized iron (CGI) sheets. This transition has triggered an urban heat island effect and severe indoor overheating. This paper analyzes the thermodynamic principles that make thatch roofs an exceptional passive cooling technology in Nigerian traditional architecture.

2 Material properties of thatch and earth

The exceptional thermal performance of traditional Nigerian dwellings is rooted in the low thermal conductivity and high specific heat capacity of the building materials employed.

2.1 The thatch roof

Thatch typically consists of dried vegetative materials such as wild grass (*Imperata cylindrica*), elephant grass (*Pennisetum purpureum*), or palm fronds (*Raphia* spp.), bound tightly over a timber framework.

- **Low Thermal Conductivity (k):** Compressed organic thatch has a remarkably low thermal conductivity, typically ranging between 0.05 and 0.08 W/(m·K). This is largely due to the high volume of trapped dry air pockets within the porous matrix. Air is a poor conductor of heat, which severely impedes conductive heat transfer from the exterior solar-heated surface to the interior ceiling plane.
- **Solar Reflectance and Emissivity:** Dry thatch has a relatively high albedo compared to weathered metal sheets and possesses high long-wave thermal emissivity, allowing it to rapidly reradiate absorbed solar energy back into the night sky through long-wave radiation.

2.2 The mud (earth) wall

Thatch rarely works in isolation; it is complemented by walls constructed from stabilized or unstabilized rammed earth (*tubali* in Hausa architecture) or wattle-and-daub. Earth boasts a high volumetric heat capacity ($\approx 1.5 \times 10^6$ J/m³·K) and a thick cross-section (often 300 mm to 500 mm). This creates a massive time-lag effect, where peak afternoon solar heat takes several hours to penetrate the interior wall surface, releasing coolness during the warm night and warmth during the chilly harmattan nights.

3 Thermodynamic mechanisms of thatch roof cooling

The cooling effect of a thatch roof is not attributable to a single property, but rather to a complex interplay of conduction resistance, phase-change dynamics (moisture evaporation), and aerodynamic ventilation.

3.1 Resistance to heat conduction and thermal damping

Fourier's Law of Thermal Conduction dictates that heat flux through a material is proportional to its thermal conductivity and the temperature gradient across it. Due to the thickness of thatch roofs (often 150 mm to 300 mm) and its negligible thermal conductivity, the decrement factor—the ratio of indoor temperature fluctuation amplitude to outdoor temperature fluctuation amplitude—is exceptionally low.

When solar radiation strikes the outer surface of the thatch, the outer layer absorbs the heat. However, because vegetative fibers lack free electrons (unlike metals), phonon-mediated heat transfer is exceptionally sluggish. Consequently, the inner surface of the thatch remains cool, preventing radiant heat from dominating the indoor microclimate.

3.2 Transpiration and evaporative cooling

In humid tropical zones, thatch roofs undergo natural micro-evaporation. During the rainy season or early morning hours, the hygroscopic nature of organic fibers allows them to absorb ambient moisture. As ambient temperatures rise during the day, this moisture evaporates.

The latent heat of vaporization is drawn directly from the surrounding air and the roof material, resulting in a localized drop in temperature right at the roof surface. This psychrometric shift prevents heat from being conducted inward.

3.3 The role of roof pitch and aerodynamics

Traditional Nigerian thatch roofs—such as those found in Tiv round huts, Yoruba compound impluvi-ums, or Northern Hausa circular dwellings—are characterized by steep roof pitches.

- **Solar Geometry:** A steep pitch reduces the incidence angle of direct solar radiation during peak midday hours, spreading the incident solar energy over a larger surface area compared to a flat or low-pitch roof.
- **Stack Effect (Chimney Effect):** The high-pitched conical or pyramidal form creates an internal volume under the roof apex. Warm air naturally rises due to buoyancy and escapes through the porous apex of the thatch or via dedicated roof vents. This continuous upward draft draws cooler air in through low-level door openings and permeable mud walls.

4 Comparative analysis: Thatch roof vs. modern corrugated iron (CGI) roof

The widespread adoption of corrugated galvanized iron (CGI) sheets in contemporary Nigerian housing has drastically degraded indoor thermal comfort. Table 1 outlines a direct comparative evaluation between traditional thatch-roofed mud houses and modern concrete-block houses with CGI roofs.

Table 1. Comparative thermal and structural analysis.

Architectural Parameter	Traditional Thatch Roof + Mud Walls	Modern CGI Roof + Concrete Block Walls
Roof Material	Dried grass/palm fronds	Corrugated Galvanized Iron
Wall Material	Rammed earth / Mud brick	Sandcrete hollow blocks
Roof Pitch	High	Low to Medium
Indoor vs. Outdoor Temp Delta	cooler than ambient	warmer than ambient (Greenhouse effect)
Thermal Lag (Time Delay)	High	Low
Radiant Heat Emission	Very low (high-emissivity, poor conductor)	Extremely high (low-emissivity, high conductor)
Indoor Air Velocity	Moderate to High (permeable envelope)	Low (air-tight sealed fenestrations)
Embodied Energy	Negligible, locally sourced, biodegradable	High, energy-intensive industrial processing
Acoustic Performance	Excellent sound absorption (heavy rain dampening)	Poor (deafening noise during tropical storms)

4.1 Advantages of mud and thatch houses in Nigerian traditional architecture

Mud and thatch houses are advantageous because they use local, low-cost materials that provide excellent thermal comfort, environmental sustainability, and deep cultural meaning across Nigerian communities.

Cultural Significance: Mud houses reflect deep-rooted cultural practices and communal activities, often built collaboratively by family and community members.

Aesthetic Appeal: Traditional mud and thatch houses often feature decorative motifs and architectural styles that are integral to the cultural identity of the communities.

4.1.1 Climate adaptation and thermal comfort

Mud and thatch were chosen because they respond exceptionally well to Nigeria's tropical and Sahel climates.

- Thick mud walls absorb heat during the day and release it slowly at night, keeping interiors cool despite intense sun in northern regions.
- Mud's **high thermal mass** and breathable surfaces regulate humidity in the humid southeast

Thatch roofs provide **natural ventilation and waterproofing**, shedding rain effectively in high-rainfall Igbo areas

These features allowed comfortable living without artificial cooling or heating.

4.1.2 Local availability and low cost

Mud, clay, grasses, palm fronds, and bamboo are **abundant across Nigeria**, making construction accessible to all social classes.

- Hausa tubali (sun-dried mud bricks) and Igbo mud walls rely on **locally sourced earth**, reducing cost and eliminating industrial processing
- Mud huts are described as **easy and cheap to build**, requiring simple tools and communal labor

This affordability made traditional housing widely attainable.

4.1.3 Sustainability and environmental benefits

Mud and thatch construction is inherently eco-friendly.

- Mud buildings are considered **green architecture**, reducing air pollution and energy use
- Materials are **biodegradable**, renewable, and require minimal carbon-intensive manufacturing
- Traditional craftsmanship supports **circular material life cycles** and reduces dependence on industrial systems

These qualities align with modern sustainability goals.

4.1.4 Durability and structural strength

Despite their simplicity, mud houses can be remarkably durable.

- Northern Nigerian mud houses were admired for toughness and ability to withstand harsh Sahel weather
- Properly plastered and maintained mud buildings can remain **structurally firm for decades**
- Thick walls also provide **sound insulation** and protection from wind and dust storms.

Historic examples include the **ancient city walls of Kano** and **Emir's palaces**, built largely from mud

4.1.5 Cultural identity and symbolism

Mud and thatch houses are deeply tied to Nigerian cultural heritage.

- Igbo compounds use mud walls and thatched roofs as part of symbolic spatial organization reflecting kinship and cosmology
- Mud huts often feature decorative motifs, uli designs, carvings, and symbolic patterns that encode history and ideology
- These structures serve as **markers of identity**, with forms indicating social status, lineage, or ritual significance (e.g., Igbo *obi*, Hausa palace designs)

They are not just shelters—they are cultural archives.

4.1.6 Communal construction and social cohesion

Building mud and thatch houses traditionally involved **collective labor**, strengthening community bonds.

- Hausa communities build mud houses through **communal activity**, with neighbors helping mold blocks and raise walls
- Igbo compounds rely on **age-grade labor and shared craftsmanship**, reinforcing social networks

This process embeds architecture within social life.

4.1.7 Flexibility and adaptability

Mud and thatch allow easy modification and repair.

- Walls can be patched with fresh mud, and thatch can be replaced seasonally.
- Designs can be round, rectangular, or conical depending on cultural preference and environmental needs.

4.2 Types of Nigerian thatch

Nigeria's thatched roofs mainly fall into palm-frond thatch, grass/reed thatch, and ethnic traditional styles such as Igbo thatched buildings, with modern synthetic thatch emerging as a newer option.

4.2.1 Core traditional types of Nigerian thatch

Nigeria's traditional roofing relies on locally sourced vegetation, especially in rural and culturally preserved communities. These materials are highlighted across multiple sources as the basis of thatch roofing

4.2.1.1 Palm-frond thatch

- Made from **palm leaves**, a common roofing material in southern and coastal regions
- Used widely in rural homes and traditional compounds
- Offers **good insulation** and is lightweight but requires frequent maintenance

4.2.1.2 Grass or reed thatch

- Constructed using **grasses, reeds, or similar vegetation** layered to shed water
- Common in inland rural communities where tall grasses are abundant.
- Provides natural cooling and is part of long-standing building traditions.

4.2.2 Ethnic and regional traditional styles

Nigeria's ethnic groups have distinct architectural traditions that shape how thatch is used.

4.2.2.1 Igbo thatched architecture

- Igbo compounds often feature thatched roofs on buildings, gateways, and awnings
- Materials include **grass, palm leaves, reeds, and bamboo**, woven to ensure drainage and ventilation
- Thatch is central to Igbo traditional building design, paired with mud or clay walls for insulation

4.2.2.2 Other regional uses

- In many rural communities across Nigeria, thatch is used for **homes, farm shelters, shrines, and communal structures**
- Northern regions may use grass-based thatch adapted for hot, dry climates.

4.2.3 Construction techniques

Across Nigeria, thatching follows similar principles:

- Vegetation is **layered and tied** to a wooden frame to shed water effectively
- Proper bundling and weaving ensure **ventilation and water resistance**
- Roof pitch is important—steeper angles improve durability and drainage

4.2.4 Durability and maintenance

- Natural thatch typically lasts **5–10 years** before re-thatching is needed
- Vulnerable to **humidity, mold, and fire**, requiring protective measures.
- Regular upkeep is essential in Nigeria's rainy and humid regions.

4.2.5 Modern alternative: Synthetic thatch

- Synthetic thatch made from **HDPE or PVC** mimics natural thatch but lasts **up to 50 years**
- Resistant to **rot, insects, and fire**, and increasingly used for resorts or themed buildings.
- Offers a long-term, low-maintenance alternative while preserving traditional aesthetics.

Table 2. Types of Nigerian thatch.

Type	Materials	Key Features	Notes
Palm-Frond Thatch	Palm leaves	Good insulation, lightweight	Common in southern/coastal regions
Grass/Reed Thatch	Tall grasses, reeds	Traditional, breathable	Used widely in rural inland areas
Igbo Traditional Thatch	Grass, palm leaves, reeds, bamboo	Cultural significance, used on buildings & gateways	Part of Igbo architectural identity
Synthetic Thatch	HDPE, PVC	Long lifespan, fire-resistant	Modern alternative gaining popularity

5 Performance in specific Nigerian typologies

To contextualize these thermodynamic principles, we examine how different ethnic groups in Nigeria harness thatch roof cooling systems:

5.1 The Tiv round hut (Middle Belt)

The Tiv compound features circular mud-walled huts capped with steep conical thatch roofs. The circular geometry eliminates stagnant corners where hot air can accumulate. The continuous perimeter wall allows uniform air distribution, while the high conical thatch roof provides a large thermal buffer zone. Field studies in central Nigeria consistently demonstrate that interior temperatures in these huts remain remarkably stable, hovering around 26 °C to 28 °C even when outdoor ambient temperatures soar past 38 °C.

5.2 Northern Nigerian vernacular (Hausa/Kanuri)

In the dry, arid north, where diurnal temperature ranges are extreme (hot days, cold nights), heavy earth walls coupled with thick thatch or vaulted mud-brick domes (*zukku*) regulate temperature fluctuations. While domes are prevalent in urban Hausa architecture, rural variants rely heavily on thick thatch layers to block intense solar radiation during the dry season.

The most widely recognized mud-and-thatch houses in Nigeria include Hausa tubali compounds, Igbo round-wall mud houses, Yoruba courtyard mud houses, Tiv circular thatched huts, Fulani suudu huts, and Gwari rectangular clay houses.

5.2.1 Hausa mud compounds (Tubali)

Hausa traditional architecture relies heavily on mud, grasses, corn stalks, and straw for thatch roofing.

- Built with **tubali** (sun-dried mud bricks).
- Thick mud walls for insulation and flat or slightly curved roofs.
- Often arranged as **family compounds** with dakis (rooms), rumfa (shade), shago (male quarters), and rijiyā (well)
- Decorative wall carvings and geometric motifs are common

5.2.2 Igbo round-wall mud houses (Ulo Aja Oto)

Igbo pre-colonial houses were round-wall mud structures with thatched roofs

- Roof frames woven from bamboo and palm fronds, then covered with grasses.
- Mud and clay are fundamental building materials in Igbo architecture.
- Compounds include obi (meeting house), shrines, and multiple rooms arranged around a courtyard

Thatched buildings (ulọ àkanya / ílò / aju) are central features

5.2.3 Yoruba mud courtyard houses (Orowa / Agbo'le)

Yoruba traditional houses use **mud or laterite walls** and **thatch or palm-leaf roofing** depending on region

- Built around a **large central courtyard**, forming extended family compounds.
- Thick mud walls provide cooling; bamboo rafters support the roof

- Known as **agbo'le**, often named after the family head.

5.2.4 *Tiv circular thatched huts (Iyol i Hira / Ate)*

Tiv architecture features circular huts with conical thatched roofs

- Walls made of mud or clay; roofs made from dry grass.
- Round shape improves wind resistance and temperature regulation.
- Used as living spaces, rest shelters, and communal gathering points.

5.2.5 *Fulani Suudu huts*

Fulani huts are round structures made from woven sticks, grass, and mud plaster

- Conical thatched roofs suited to the hot Sahel climate.
- Lightweight and designed for easy dismantling due to nomadic lifestyle.

5.2.6 *Gwari (Gbagyi) rectangular mud houses*

Gwari houses are rectangular clay-and-straw structures with thatched roofs

- Straight walls and slanted thatch roofing.
- Decorated with natural pigments and geometric motifs.
- Built for efficient space division within family compounds.

6 Challenges and modern adaptations

Despite their superior thermal performance, traditional thatch roofs face significant socio-technical hurdles in contemporary Nigeria:

1. **Durability and Maintenance:** Thatch is susceptible to biodegradation, insect infestation (termites), and fungal rot, requiring regular maintenance or complete re-thatching every 3 to 7 years.
2. **Fire Hazard:** Dry vegetative materials present a high fire risk, particularly in densely packed settlements or during the dry harmattan season.
3. **Perception of Poverty:** Thatch is socio-culturally stigmatized as "primitive," driving urban and rural populations toward modern materials regardless of thermal consequences.

6.1 Toward biophilic and hybrid solutions

Modern sustainable architecture in the tropics can draw inspiration from these vernacular techniques without replicating purely primitive construction methods. Innovations include:

- **Insulated Composite Roofs:** Integrating modern waterproofing membranes with natural vegetative layers beneath metallic or slate roof decks.
- **Double-Skin Roofs:** Creating ventilated air cavities beneath CGI roofs to mimic the stack effect of high-pitched traditional roofs.
- **Chemically Treated Thatch:** Applying eco-friendly fire retardants and biostabilizers to extend the lifespan of organic roofing materials.

7 Conclusion

The thatch roof in Nigerian traditional architecture is not merely a primitive shelter component, but a highly evolved, environmentally responsive thermodynamic system. Through a combination of low thermal conductivity, high specific heat capacity, evaporative cooling, and aerodynamic high-pitched geometry, thatch roofs successfully mitigate intense tropical solar radiation.

As Nigeria faces escalating energy crises and the urban heat island phenomenon, re-evaluating and modernizing indigenous passive cooling strategies—specifically the integration of thatch and earth thermal dynamics—offers a viable pathway toward low-carbon, thermally comfortable, and culturally resonant architecture.

References

- [1] Akinbamijo OB (2000). Microclimatic conditions and thermal comfort in traditional dwellings in southwestern Nigeria. *Journal of Environmental Technology*, 4(1), 45–52.
- [2] Aliyu AS, Dada JO, Aliyu I (2015). Indigenous architecture and sustainable thermal comfort in Nigeria: A review. *Nigerian Journal of Environmental Sciences and Technology*, 2(1), 112–124.
- [3] Givoni B (1998). Climate Considerations in Building and Urban Design. *Van Nostrand Reinhold*.
- [4] Jatau D (2012). The physics of vernacular architecture: Thermal performance of mud and thatch structures in the savannah belt of Nigeria. *Journal of Architectural Research and Development*, 8(3), 89–104.
- [5] Ojo A (2016). Sustainable building materials in West Africa: Properties of earth and organic thatch. *International Journal of Tropical Construction*, 11(2), 201–215.
- [6] Olgyay V (1963). Design with Climate: Bioclimatic Approach to Architectural Regionalism. *Princeton University Press*.