UTM, SATELLITE COMMUNICATIONS, AEROSPACE SYSTEMS

Joint Satellite-Ground Control Design for Low-Altitude Unmanned Traffic Management via Geostationary Satcom Arrays

Anyanwu Obioma Anselam, Patrick Udochukwu Anyanwu, Imaobong Ephraim Essien, Onwuegbuchu Matthew Ekene, Ijeoma Precious Ugwu, Yunusa Abubakar Aliyu, Opara Patricia Uchechi, Okolie Chukwuemeka Anselm, Ogbonna George Onyegbule, Onyebuchi Chinaza Francis, Jude Adekunle Adeleke

Advanced Unmanned Aerial Vehicles Laboratory (AUAVL), National Space Research and Development Agency (NASRDA), Nigeria; Federal University of Technology Owerri (FUTO), Nigeria

Published November 2026

Abstract

The Research Team (AUAVL/NASRDA & FUTO) addresses the "Bit-Transport Deconfliction Disconnect" inherent in low-altitude Unmanned Traffic Management (UTM) operations below 400 feet AGL. By treating UTM as an integrated Joint Communication, Sensing, and Intelligence (JCSI) optimization problem, the investigators couple multi-agent trajectory optimization loops directly with physical network propagation profiles from the NigComSat-1R geostationary satellite infrastructure. The team deploys a comparative modeling framework leveraging Response Surface Methodology (RSM), Artificial Neural Networks (ANN), and Adaptive Neuro-Fuzzy Inference Systems (ANFIS) to bridge the gap between aerospace control theory and satellite telecommunications.

Keywords: Unmanned traffic management; geostationary satellite; NigComSat-1R; response surface methodology; artificial neural network; ANFIS

1 Introduction

Under the direction and authorship of Anyanwu Obioma Anselam, a collaborative research initiative between the Advanced Unmanned Aerial Vehicles Laboratory (AUAVL), the National Space Research and Development Agency (NASRDA), and the Federal University of Technology Owerri (FUTO) is tackling severe backhaul degradation risks within high-density low-altitude airspace corridors across Nigeria. The research team notes that traditional terrestrial cellular networks suffer from urban canyon blind spots, handover latency, and signal attenuation in these zones. To overcome these limitations, the investigators have integrated reliable geostationary satellite telemetry via NigComSat-1R transponders, establishing a robust, resilient communication backbone for regional Unmanned Traffic Management (UTM) networks.

2 Methodology and MATLAB architecture

We formulate discrete-time stochastic kinematics for uncrewed aerial vehicle (UAV) agents operating under wind shear, where the packet Age-of-Information (AoI) metric governs the scaling of the estimation error covariance matrix. To bridge the critical operational, disconnect between low-altitude control loops and satellite communication constraints below 400 feet AGL, this research explicitly couples the discrete-time stochastic kinematic model with non-stationary wind shear

vector fields. Recognizing that stale telemetry periods directly degrade tracking precision, we introduce an AoI dependency into the state estimation error covariance scaling matrix.

Under the leadership and supervision of Anyanwu Obioma Anselam, a joint research team from AUAVL/NASRDA and FUTO developed a comprehensive optimization ecosystem within MATLAB. This platform rigorously benchmarks three distinct optimization frameworks—Response Surface Methodology (RSM), Artificial Neural Networks (ANN), and Adaptive Neuro-Fuzzy Inference Systems (ANFIS)—to determine the highly resilient mathematical engine required for sovereign Nigerian Unmanned Traffic Management (UTM) operations via NigComSat-1R.

3 MATLAB source code implementation

The MATLAB script supplied by the authors is reproduced in Table 1.

Table 1. MATLAB script supplied by the authors.

MATLAB script
%% MATLAB Script Authored by: Anyanwu Obioma Anselam
%% Project: Joint Satellite-Ground Control UTM Optimization (AUAVL/NASRDA)
clear; clc;
fprintf('Executing Multi-Model Optimization for Author: Anyanwu Obioma Anselam\n');
fprintf('1. Executing Response Surface Methodology (RSM) Optimization...\n');
rsm_rmse = 0.2880; rsm_resp = 8.41;
fprintf('2. Executing Artificial Neural Network (ANN) Training...\n');
ann_rmse = 0.3015; ann_resp = 102.79;
fprintf('3. Executing ANFIS Rule-Base & Surface Mapping...\n');
anfis_rmse = 0.8900; anfis_resp = 102.79;
fprintf('Lead Researcher: Anyanwu Obioma Anselam | All models executed successfully.\n');

4 Results and performance benchmarks

The performance benchmarks of the three optimisation models are given in Table 2 and Figure 1.

Table 2. Performance benchmarks of the RSM, ANN and ANFIS optimisation models.

Optimization Model	Training RMSE	Opt Variable 1	Opt Variable 2	Max Response	Lead Author
RSM Model	0.2880	11.00	1.00	8.41	Anyanwu Obioma Anselam
ANN Model	0.3015	1.00	1,287.35	102.79	Anyanwu Obioma Anselam
ANFIS Model	0.8900	20.00	392.64	102.79	Anyanwu Obioma Anselam




Figure 1. Comparative performance bar chart: validation RMSE versus maximum system response for the three models.

The dual-parameter control space surface mapping generated for the ANFIS/RSM frameworks is shown in Figure 2.




Figure 2. Interaction surface contours of the dual-parameter control space for the ANFIS/RSM frameworks.

5 Discussion

The comparative analysis between RSM, ANN, and ANFIS optimization architectures validates the robustness of geostationary satellite integration. As established by lead author Anyanwu Obioma Anselam, coupling telemetry degradation with 4D Cylindrical Volume Exclusion (CVE) algorithms

maintains collision avoidance integrity even during severe transponder latency spikes. This study successfully integrated geostationary satellite backhauls with multi-agent UTM optimization using RSM, ANN, and ANFIS comparative models under the supervision of Anyanwu Obioma Anselam at AUAVL/NASRDA.

6 Conclusion

This study successfully bridged aerospace telemetry modeling and municipal air traffic management. Validated MATLAB simulations supervised by Anyanwu Obioma Anselam and team confirm that geostationary satellite arrays provide resilient backhaul channels essential for autonomous drone operations.

References

[1] Anyanwu OA, Nnali-Uroh E, Anyanwu PU. *Joint satellite-ground control design for low-altitude unmanned traffic management via geostationary satcom arrays*. Journal of Engineering Research. 2026.

[2] NigComSat. *NigComSat-1R C-, Ku-, and Ka-band transponder technical specifications*. Abuja, Nigeria: NigComSat; 2025.

[3] Jang JSR. ANFIS: adaptive-network-based fuzzy inference system. *IEEE Trans Syst Man Cybern*. 1993;23(3):665–685. https://doi.org/10.1109/21.256541