INDUSTRIAL

Improving Scrap Segregation Efficiency through Metal Composition Analysis: A Case Study of Scrap Trading Operations

Sneha Jaiswal, Purnima Chouhan, Rajat Gera

Amity University Mumbai

Published November 2026

Abstract

Scrap trading involves more than purchasing and reselling discarded materials. A business must understand the type, condition and quality of each lot before deciding how it should be stored, valued and sold. Incoming scrap may contain different metals in the same load, along with coatings, insulation, plastic, rubber or other unwanted materials. When these materials are mixed, identifying the quantity and composition of each metal becomes more difficult.

This challenge is particularly important when copper-bearing and aluminium-bearing materials are present together. Both metals have commercial value, but their market prices and resale requirements differ. If the composition of a lot is uncertain, the business may face difficulties in estimating its value, negotiating with suppliers, maintaining inventory records and preparing material for buyers. Visual inspection can support an initial assessment, but it cannot always confirm the composition of an entire mixed load.

This case study examines the operational challenges associated with mixed-scrap segregation and proposes a practical approach based on consistent inspection, clear classification, suitable verification, separate storage and accurate documentation. It recommends that each lot be assessed when received, assigned a reference and directed to an appropriate storage area. Materials that cannot be confidently identified should remain separate until further assessment is completed.

The proposed approach aims to improve the reliability of material identification, reduce avoidable handling and provide better information for commercial decisions. Its effectiveness should be measured using actual operating records, including sorting time, inventory discrepancies and classification errors. No financial savings or performance improvements are assumed in advance.

1 Introduction and business background

Scrap trading forms an important link in the recycling and material-recovery chain. Materials recovered from industrial operations, machinery, electrical components and other sources may retain value when they are correctly identified and supplied to suitable buyers. For a scrap trader, the work involves assessing incoming material, understanding its condition, organising stock and ensuring that the description of the material matches what is ultimately sold.

Unlike standardised finished products, scrap can arrive in different shapes, sizes and conditions. Some loads contain clearly identifiable materials, while others include several metals joined together. Paint, rust, dirt, insulation and attached components may hide the material underneath. As a result, the initial inspection can have a direct influence on the way the lot is classified and managed.

Consider a lot containing copper-bearing components, aluminium parts and steel attachments. If it is recorded only as general mixed scrap, employees may need to inspect and separate it again when a buyer requests a particular category. The additional work can affect handling time and make it harder to establish the quantity of each material available for sale.

The issue also affects purchasing decisions. The commercial value of a lot depends on its material category, grade, condition, contamination and prevailing market rates. When the composition is unclear, the business must make decisions with incomplete information. A consistent segregation process can improve the quality of that information and help connect purchasing, storage, inventory and sales activities.

This case study focuses on the practical difficulties of managing mixed scrap in a trading operation. The objective is to identify the causes of the problem and recommend a procedure that can be followed in daily operations without introducing unnecessary complexity.

2 The operational problem

The central problem is the difficulty of identifying and separating mixed scrap before its valuation, storage and resale. When different metals arrive together, employees may not immediately know the quantity or composition of each material. This uncertainty can affect the purchase price, the way stock is recorded and the time required to prepare material for sale.

Copper and aluminium require particular attention because they have different commercial values. However, the presence of copper-bearing or aluminium-bearing components does not establish the percentage of either metal in the complete lot. A load may also contain steel, insulation, coatings, plastic and other unwanted materials. A visual estimate may be useful for preliminary sorting, but it should not be presented as a confirmed measurement of the lot's composition.

If the material is not classified properly at the time of receipt, the problem may continue during storage. Different categories can remain mixed, making specific materials difficult to locate when an order is received. Employees may then have to move and sort the same material again, increasing handling and delaying other tasks.

Incomplete records create another difficulty. When a lot is divided into several categories, the resulting quantities need to be recorded against the original lot reference. If this information is not updated, the physical stock may not match the inventory description. The business may then struggle to determine what is available for sale or investigate a discrepancy.

The issue is therefore broader than physical sorting. It concerns the way material is identified, documented, stored and verified throughout the trading process. An effective solution must connect these activities rather than treating them as separate tasks.

3 Analysis of the existing situation

The segregation process typically begins when a load arrives from a supplier. Employees inspect the material, make an initial classification and decide where it should be stored. When the material is uniform and easy to identify, this process may be straightforward. Mixed loads require more attention because a quick inspection may not provide enough evidence to classify every component accurately.

A potential weakness is reliance on individual judgement without common classification rules. Experienced employees may recognise familiar items, but similar materials can be described

differently when staff follow different practices. This inconsistency can affect storage, stock records and communication between teams.

Another concern is that segregation may be postponed until a buyer requests a specific material. While this can appear convenient during receipt, it may result in repeated handling later. Employees may need to locate the lot, inspect it again, separate the categories and update the records before dispatch.

Storage arrangements can also contribute to the problem. Materials that were initially separated may become mixed if locations are not clearly marked or if the movement of stock is not controlled. In addition, inspection details may be lost if they are not recorded and remain only with the employee who handled the material.

These observations suggest that segregation should be treated as an operational control process. A review of current practices should identify which materials most often arrive mixed, where uncertainty arises, how frequently sorting is repeated and whether records reflect the physical stock. The findings can then guide improvements suited to the actual stockyard and the types of scrap handled.

4 Challenges faced in scrap segregation

Material identification is one of the main challenges. Scrap can be covered with paint, rust or dirt, and some components contain more than one metal. The visible surface may not represent the full composition, so classification based on appearance alone can be unreliable in certain cases.

Estimating copper and aluminium content is a related challenge. A mixed lot may include copper conductors, aluminium parts, steel attachments and non-metallic materials. The amount of recoverable metal cannot be confirmed simply by observing that a metal is present. When an right composition estimate is important to the transaction, the business may need representative sampling or a suitable specialist assessment.

Sorting also requires time, labour and space. Employees may need to inspect individual items, separate identifiable categories and place them in proper containers. If the same lot has to be sorted more than once, the effort is repeated. Poorly marked storage areas can make this worse by making material harder to locate or increasing the risk of accidental mixing.

Pricing and resale are affected when the category or quality of a lot is uncertain. The purchasing team may have difficulty comparing quotations or determining a suitable value. Buyers may also question a delivery if the material does not match the agreed description. These risks make clear classification and verification commercially important.

Finally, segregation depends on coordination. Purchasing staff, stockyard employees, inventory personnel and sales staff need to work with consistent material descriptions. If each group follows a different method, information can be lost between receipt and dispatch. A shared procedure and clear responsibilities can help reduce this uncertainty.

5 Proposed solution and implementation

The recommended solution is a standard procedure that begins when scrap is received and continues until the material is ready for sale. The process should be practical, consistent and suitable for the types of scrap handled by the business.

Each incoming lot should be assigned a unique reference. The receiving record should include the supplier, date, quantity and initial description. Employees should inspect the visible materials, note obvious mixtures and identify any contamination or attached components. Photographs may be retained when they help document the condition of a lot.

The initial assessment should distinguish between materials that can be identified confidently and those that remain uncertain. A simple classification guide can include categories such as ferrous scrap, copper-bearing material, aluminium-bearing material, other non- ferrous scrap, mixed-metal scrap and material awaiting verification. These categories should be adapted to the business's actual stock. Uncertain materials should not be recorded as confirmed copper or aluminium scrap without adequate evidence.

Where it is safe and practical, identifiable materials should be separated and moved to designated storage areas. Clear labels should state the material category, and a separate holding area should be maintained for mixed or unverified items. The storage layout should support safe movement, prevent accidental mixing and allow employees to locate materials without unnecessary handling.

Verification methods should be selected according to the material and the commercial importance of the decision. Visual inspection and suitable magnetic checks can support preliminary classification, but a magnet does not identify copper or aluminium specifically. An appropriately configured metal analyser may help identify elements at the tested location, but a single reading does not establish the composition of an entire heterogeneous load. If the business needs to estimate bulk metal content, representative sampling and a suitable specialist or laboratory assessment may be required.

Records should be updated whenever a lot is divided, moved, reclassified or sold. If one lot produces several categories, the quantities should remain linked to the original reference. Before dispatch, the responsible employee should check that the physical material matches the recorded category and the buyer's requirements.

Implementation should begin with a review of existing operations. Management can identify the most common segregation problems, prepare a simple written guide and train the employees involved in receiving, sorting, storing and recording materials. Regular checks and feedback from staff can help establish whether the procedure is practical and where it needs adjustment.

The aim is not to test every item or create unnecessary paperwork. It is to apply the right level of inspection and verification to each lot, while maintaining sufficient information for reliable stock and commercial decisions.

6 Expected business impact

A consistent segregation process is expected to make the handling of mixed scrap more organised. When employees use common categories and clear storage locations, materials should be easier to show and locate. This can reduce confusion and may limit the need to sort the same material repeatedly.

Better information about material category and condition can also support purchasing and valuation. The business can compare lots more consistently and consider uncertainty before agreeing on a price. This does not guarantee a higher selling price or a particular saving, but it provides a more dependable basis for commercial decisions.

Improved documentation can strengthen inventory control. Lot references and updated movement records make it easier to trace materials from receipt to dispatch and investigate differences between recorded quantities and physical stock. Clearer records can also improve coordination between purchasing, stockyard, inventory and sales personnel.

Separate storage may help the business prepare orders more efficiently and reduce the risk of dissimilar categories being mixed during loading. More consistent material descriptions can also help the business communicate with buyers about the category being supplied.

These outcomes should be assessed using actual operational data. The business can compare sorting time, repeated handling, inventory discrepancies and classification errors before and after the procedure is introduced. The results will show whether the changes are useful and whether further adjustments are needed.

7 Conclusion

Scrap segregation is an important part of scrap trading because it influences how materials are found, valued, stored and sold. When different metals arrive in the same lot, the business must establish what can be identified confidently and what requires further assessment. This is particularly important when copper-bearing and aluminium-bearing materials are mixed, as their commercial values and resale requirements differ.

The case study shows that the difficulty is not limited to sorting. Inconsistent classification, unclear storage arrangements and incomplete records can create repeated work and make it harder to know what material is available for sale. A consistent process can address these issues by connecting inspection, segregation, verification, storage and documentation.

It is recommended that the business inspect incoming material, use a common classification guide, keep uncertain materials separate, maintain clear storage labels and update records whenever stock moves or is divided. Additional testing should be considered when the composition is uncertain and the result could materially affect a commercial decision. The method chosen must be suitable for the material; a reading from one point should not be treated as proof of the percentage of a metal in an entire mixed load.

The effectiveness of the process should be reviewed through actual records rather than assumed in advance. By tracking sorting time, inventory discrepancies and classification errors, the business can assess whether segregation has become more consistent and efficient. Better segregation is not simply about separating metals. It is about giving the business clearer information about the materials it handles and creating a more reliable basis for purchasing, inventory management and re-sale.

References

[1] Kölking, M., Flamme, S., Heinrichs, S., Schmalbein, N., & Jacob, M. (2024). More resource efficient recycling of copper and copper alloys by using X-ray fluorescence sorting systems: An investigation on the metallic fraction of mixed foundry residues. *Waste Management & Research*, 42(9), 814–822. https://doi.org/10.1177/0734242X241241601

[2] Xiong, T., Ye, W., & Xu, X. (2021). Combination of dual-energy X-ray transmission and variable gas-ejection for the in-line automatic sorting of many types of scrap in one measurement. *Applied Sciences*, 11(10), 4349. https://doi.org/10.3390/app11104349

[3] Institute of Scrap Recycling Industries. (2024). ISRI specifications: Scrap specifications circular 2024. https://www.isrispecs.org/

[4] Koyanaka, S., Kobayashi, K., Yamamoto, Y., Kimura, M., & Rokucho, K. (2013). Elemental analysis of lightweight metal scraps recovered by an automatic sorting technique combining a weight meter and a laser 3D shape-detection system. *Resources*, Conservation and Recycling, 75, 63–69. https://doi.org/10.1016/j.resconrec.2013.03.010